

SLIDE LOCK SPRING FOR GLOCK® FULLSIZE PISTOLS - BROWNELL'S

SLIDE LOCK SPRING FOR GLOCK® 17, 22, 34, & 35

[Handgun Parts](#) > [Frame Parts](#) > [Slide Catch Parts](#) > [Slide Catch Springs](#)

Replacement slide lock spring for Glock® fullsize pistols.



Attributes

- Name: [BROWNELL'S SLIDE LOCK SPRING FOR GLOCK® 17, 22, 34, & 35](#)
- Manufacturer: [BROWNELL'S](#)
- Product no.: 078000657
- Mfr. No.: 02-1066-02-00
- Model: 22,17,35,34
- Weapon type: Glock
- Delivery weight: 0.005kg
- Shipping height: 76mm
- Shipping width: 3mm
- Shipping length: 165mm
- UPC: 050806004177

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for SLIDE LOCK SPRING FOR GLOCK® FULLSIZE PISTOLS
- About Us

Safety Instruction Guide for SLIDE LOCK SPRING FOR GLOCK® FULLSIZE PISTOLS

Introduction

Thank you for purchasing the Slide Lock Spring for Glock® Fullsize Pistols. This guide provides important safety information, installation instructions, and usage precautions to ensure your safety and the proper functioning of your firearm.

General Safety Guidelines

- Always follow the manufacturer's instructions for your firearm.
- Ensure that the firearm is unloaded before performing any maintenance or installation.
- Store the slide lock spring and all firearm components out of reach of children and unauthorized users.
- Regularly inspect your firearm and its components for wear and damage.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

• Identification of Hazards:

- Improper installation of the slide lock spring can lead to malfunction of the firearm.
- Using a damaged or worn slide lock spring may compromise the safety and performance of the firearm.

• Instructions for Avoiding Hazards:

- Ensure that you are using the correct slide lock spring for your specific Glock® model (17, 22, 34, 35).
- Always wear safety glasses when handling or working on your firearm.
- If you are unsure about the installation process, seek assistance from a qualified gunsmith.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is completely unloaded.
- Gather necessary tools: a punch tool and a small hammer.

2. Installation Steps:

- Remove the slide from the frame of the Glock® pistol.
- Locate the existing slide lock spring and gently remove it using the punch tool.
- Take the new slide lock spring and align it with the slide lock mechanism.
- Carefully insert the new slide lock spring into place, ensuring it is seated correctly.
- Reattach the slide to the frame of the pistol.

3. Usage Instructions:

- After installation, perform a function check to ensure the slide lock operates correctly.
- Regularly inspect the slide lock spring during routine maintenance.

Disposal Instructions

- Dispose of the old slide lock spring and any packaging materials in accordance with local regulations.
- Do not dispose of any firearm components in regular household waste. Check with local authorities for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the slide lock spring or its installation, please consult a qualified gunsmith or reach out to the manufacturer for assistance. Always ensure that you are using genuine parts designed for your specific firearm model.

Thank you for ensuring the safety and functionality of your Glock® Fullsize Pistol. Your adherence to these safety guidelines is crucial for responsible firearm ownership.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk