

AR-15 SLING ADAPTER - MIDWEST INDUSTRIES LOOP SLING ADAPTER

[Shooting Accessories](#) > [Slings & Sling Swivels](#) > [Tactical Sling Mounts](#)

Installs Easily; Choose Your Sling Position On Collapsible Stocks

Hard anodized, 6061 aluminum sling adapter clamps to collapsible stock buffer tubes with no need for special tools or to remove the buffer tube. Two models available: Loop for claw-type clasp. Adapters can be used with single-point, two-point, or three-point tactical slings and are ambidextrous for use with right- or left-hand operation. Does not interfere with normal operation of collapsible stock.



Attributes

- Name: [MIDWEST INDUSTRIES LOOP SLING ADAPTER](#)
- Manufacturer: [MIDWEST INDUSTRIES](#)
- Product no.: 100002123
- Mfr. No.: MCTAR-13
- Colour: Matte Black
- Material: Steel
- Style: Rifle Sling Adapter
- Weapon type: AR-15
- Delivery weight: 0.113kg
- Shipping height: 20mm
- Shipping width: 102mm
- Shipping length: 122mm
- UPC: 816537012139

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [AR15 Sling Adapter Safety Instruction Guide](#)
- [About Us](#)

AR15 Sling Adapter Safety Instruction Guide

Introduction

Thank you for choosing the AR15 Sling Adapter by Midwest Industries. This product is designed for safe and effective use with your rifle. Please read this safety instruction guide carefully to ensure proper installation and usage, and to help you avoid potential hazards.

General Safety Guidelines

- Always ensure the firearm is unloaded before installing or using the sling adapter.
- Follow all local laws and regulations regarding firearm accessories.
- Use the sling adapter only as intended and specified in this guide.
- Regularly inspect the sling adapter for signs of wear or damage before each use.
- Keep the sling adapter and all firearm accessories out of reach of children and unauthorized users.
- If you experience any issues with the sling adapter, discontinue use immediately and seek assistance.

Specific Safety Precautions for Use

- Ensure that the sling adapter is securely attached to the buffer tube before use.
- Do not exceed the weight limit of the sling and adapter when using.
- Avoid using the sling adapter in extreme weather conditions that may affect performance.
- When transitioning between shooting positions, ensure that the sling does not become tangled or obstruct movement.
- Be aware of your surroundings and ensure that the firearm is pointed in a safe direction at all times.

Instructions for Installation and Usage

1. Installation

- Ensure the firearm is unloaded and in a safe environment.
- Locate the buffer tube on your collapsible stock.
- Align the sling adapter with the buffer tube, ensuring the clamps fit securely.
- Tighten the clamps by hand until they are snug. No special tools are required.
- Check that the adapter is firmly attached by gently pulling on it.

2. Usage

- Attach your tactical sling to the loop of the sling adapter.
- Adjust the sling to your preferred length and comfort level.
- Ensure that the sling does not obstruct access to the firearm's controls.
- When not in use, store the firearm and sling adapter in a secure location.

Disposal Instructions

- Dispose of the AR15 Sling Adapter in accordance with local regulations regarding metal recycling.
- Do not dispose of the product in general household waste.
- If the sling adapter is damaged beyond repair, consider contacting a local recycling center for proper disposal methods.

Contact Information for Further Support

For questions or concerns regarding the AR15 Sling Adapter, please refer to the product packaging or visit the

manufacturer's website for additional resources and support.

Thank you for your attention to these safety guidelines. Your safety and the safety of others is our highest priority. Enjoy your AR15 Sling Adapter responsibly.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk