

POLYMER ARMORER'S BLOCK & TOOLING PLATE - APEX TACTICAL SPECIALTIES INC APEX POLYMER ARMORER'S BLOCK

[Gunsmith Tools](#) > [Handgun Tools](#) > [Bench & Vise Blocks](#)

Supports a polymer frame pistol for armory work and detail disassembly.

Pre-positioned bosses, slots and holes remove pressure from critical function surfaces while pins are driven in and out. Thumb Safety and Magazine disconnect drop into holes and slots to prevent damage no matter what position they are in. High Density Polymer construction prevents marring of the frame while driving pins in and out. Retaining slots on each side of the block hold the striker making removal and installation of the striker spring a breeze. One side is for the 45 striker and the other is for the 9/40/357 striker. Moveable bosses are easily adjustable to position frames quickly and easily. Raised walls on each side of the block position the trigger bar within the trigger to easy trigger swapping. Apex logo and contact information cast directly into the body of the block for easy identification and access to Apex's tech support staff. The Armorer's Tooling Plate is designed to attach directly to the underside of the Apex Polymer Armorer's Block, providing a raised surface for you to work on your M&P and Glock Pistols. The tooling plate has snap locks and slots to hold the 1/8" custom roll pin punch and 1/16" allen wrench. Rubber feet grip the work surface, allowing for a sturdy hold while working. a ring magnet on the underside of the plate will prevent magnetic parts from escaping.



Attributes

- Name: [APEX TACTICAL SPECIALTIES INC APEX POLYMER ARMORER'S BLOCK](#)
- Manufacturer: [APEX TACTICAL SPECIALTIES INC](#)
- Product no.: 100011660
- Mfr. No.: 104-001
- Make: -
- Model: -
- Delivery weight: 0.091kg
- Shipping height: 43mm
- Shipping width: 132mm
- Shipping length: 206mm
- UPC: 856008005284

Item details

Made in USA

Table of Contents

- Startpage
- POLYMER ARMORER'S BLOCK & TOOLING PLATE Safety Instruction Guide
- About Us

POLYMER ARMORER'S BLOCK & TOOLING PLATE Safety Instruction Guide

Introduction

Thank you for choosing the POLYMER ARMORER'S BLOCK & TOOLING PLATE from APEX TACTICAL SPECIALTIES INC. This product is designed to assist in the maintenance and assembly of your firearms, specifically M&P and Glock pistols. To ensure your safety and the safe use of this product, please read and follow the guidelines outlined in this instruction manual.

General Safety Guidelines

- Ensure that the product is used in a wellventilated area.
- Always wear appropriate personal protective equipment (PPE) such as safety glasses and gloves when using the product.
- Keep the work area clean and free of obstructions to prevent accidents.
- Store the product out of reach of children and vulnerable individuals.
- Regularly inspect the product for any signs of wear or damage. Do not use if damaged.
- Follow all local laws and regulations regarding firearm maintenance and safety.

Specific Safety Precautions for Use

- **PrePositioned Bosses and Slots:** Ensure that all pins are properly seated in the bosses, slots, and holes before applying force. This will help prevent damage to critical function surfaces.
- **Handling Pins:** Always use the appropriate tools (such as the 1/8" custom roll pin punch) to drive pins in and out. Avoid using excessive force.
- **Thumb Safety and Magazine Disconnect:** Ensure that the thumb safety and magazine disconnect are properly seated in their respective holes to avoid accidental disengagement.
- **Striker Removal and Installation:** Use the retaining slots on each side of the block to securely hold the striker. Follow the manufacturer's instructions for removal and installation to avoid injury.
- **Trigger Bar Positioning:** Ensure that the trigger bar is correctly positioned within the trigger before attempting to swap triggers.

Instructions for Installation and Usage

1. Setting Up the Armorer's Block:

- Place the POLYMER ARMORER'S BLOCK on a stable work surface.
- Ensure that the rubber feet are securely gripping the surface to prevent slipping during use.

2. Using the Tooling Plate:

- Attach the Armorer's Tooling Plate to the underside of the Armorer's Block using the snap locks.
- Ensure that the tooling plate is securely fastened before use.

3. Adjusting Moveable Bosses:

- Adjust the moveable bosses to fit the frame of your firearm. This will help position the firearm securely while you work.

4. Driving Pins:

- Use the appropriate roll pin punch and allen wrench stored in the tooling plate.

- Align the punch with the pin and apply gentle pressure to drive the pin in or out.

5. Striker Spring Removal:

- To remove the striker spring, ensure that the striker is held securely in the retaining slots.
- Follow the specific instructions for your firearm model to avoid damage.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- If the product is damaged beyond repair, consider recycling materials where possible.

Contact Information for Further Support

For any inquiries regarding the POLYMER ARMORER'S BLOCK & TOOLING PLATE, including safety concerns or product support, please refer to the contact information provided on the product packaging or the manufacturer's website.

Conclusion

By following these safety instructions, you can ensure a safe and effective experience while using the POLYMER ARMORER'S BLOCK & TOOLING PLATE. Always prioritize safety and adhere to local laws regarding firearm maintenance. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk