

OPTIMA/JPOINT HANDGUN MOUNTS - EGW OPTIMA/JP MOUNT FOR GOLD CUP

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

EGW Optima/JPoint/Delta Point Mount. Simply remove the rear sight on your gun and replace it with the EGW mount in order to mount your Optima, J-Point or Delta Point red-dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included.



Attributes

- Name: [EGW OPTIMA/JP MOUNT FOR GOLD CUP](#)
- Manufacturer: [EGW](#)
- Product no.: 296000342
- Mfr. No.: 49421
- Color: Black
- Make: -
- Material: -
- Model: -
- Model Number: -
- Delivery weight: 0.018kg
- UPC: 841370107261

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for EGW Optima/JPoint Handgun Mount](#)
- [About Us](#)

Safety Instruction Guide for EGW Optima/JPoint Handgun Mount

Introduction

Thank you for choosing the EGW Optima/JPoint/Delta Point Mount for your Gold Cup handgun. This guide provides essential safety instructions and information to ensure the safe installation and use of your product. Please read this document carefully before proceeding.

General Safety Guidelines

- Ensure that the mount is compatible with your specific handgun model before installation.
- Always handle firearms with care and in accordance with local laws and regulations.
- Store the mount and any related accessories in a safe place, out of reach of children and unauthorized persons.
- Regularly inspect the mount and the firearm for any signs of wear or damage. If any issues are found, cease use immediately and consult a qualified gunsmith.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Only use the EGW mount with the specified red dot sights (Optima, JPoint, or Delta Point).
- Do not attempt to modify the mount or the firearm in any way that is not described in this guide.
- Ensure that the firearm is unloaded before starting the installation process.
- Follow all manufacturer guidelines for the red dot sight being used with the mount.
- If you are unfamiliar with firearm modifications, seek assistance from a qualified professional.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including a screwdriver and the mounting hardware provided with the EGW mount.
- Ensure the firearm is unloaded and pointed in a safe direction.

2. Removing the Rear Sight

- Locate the rear sight on your handgun.
- Carefully remove the rear sight using the appropriate tool, following the manufacturer's instructions.

3. Installing the EGW Mount

- Align the EGW mount with the sight base on your handgun.
- Use the provided mounting hardware to secure the mount in place. Ensure that it is tightened securely but do not overtighten.

4. Mounting the RedDot Sight

- Follow the manufacturer's instructions to attach your Optima, JPoint, or Delta Point red dot sight to the EGW mount.
- Check that the sight is securely attached and properly aligned.

5. Final Inspection

- Once the installation is complete, inspect the mount and sight to ensure everything is secure.
- Conduct a function check of the firearm to ensure proper operation.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste management regulations.
- If the mount is no longer needed or is damaged beyond repair, dispose of it responsibly to minimize environmental impact.

Contact Information for Further Support

For any questions or concerns regarding the EGW Optima/JPoint Handgun Mount, please contact the manufacturer or a qualified professional for assistance. Always refer to the product documentation for specific guidance related to your firearm and accessories.

Thank you for your attention to these safety instructions. Your safety is our priority.

About Us

Brownells Europe

Brownells Europe - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

P.O.Box 4300
Warwick
CV34 9BR

www.brownells.eu