

S&W ADJUSTABLE REAR SIGHT TRIJICON RMR SIGHT MOUNT - EGW REAR ADJ SIGHT MOUNT FOR TRIJICON RMR FITS S&W 1911 BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780" Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR, Holosun HS507C This mounts fits: Baby Desert Eagle (Post 2006) EAA Witness Elite Match This mount does not fit: Rock Island 1911s Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Flat Head Cap Screws - Provided for Trijicon RMR The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW REAR ADJ SIGHT MOUNT FOR TRIJICON RMR FITS S&W 1911 BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000594
- Mfr. No.: 49535
- Colour: Black
- Material: Aluminum
- Model: 1911
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Smith & Wesson
- Delivery weight: 0.036kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116881

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for S&W Adjustable Rear Sight Trijicon RMR Sight Mount
- About Us

Safety Instruction Guide for S&W Adjustable Rear Sight Trijicon RMR Sight Mount

Introduction

Thank you for choosing the S&W Adjustable Rear Sight Trijicon RMR Sight Mount. This guide provides essential safety instructions and installation details to ensure proper use and maintenance of your product. Please read this guide carefully to maximize safety and performance.

General Safety Guidelines

- Ensure that the product is used only as intended.
- Regularly inspect the sight mount for any signs of wear or damage.
- Keep the sight mount out of reach of children and vulnerable individuals.
- Do not use the sight mount if damaged or if any components are missing.
- Always follow the manufacturer's instructions for installation and use.
- Report any unsafe conditions or incidents to the appropriate authorities.

Specific Safety Precautions for Use

• Potential Hazards:

- Improper installation may lead to the sight mount detaching during use, posing a risk of injury.
- Using incompatible red dot sights may result in malfunction or damage.

• Avoiding Hazards:

- Ensure that the rear sight is completely removed before installing the EGW Sight Mount.
- Use the provided mounting hardware and ensure all screws are tightened to the specified torque.
- Do not exceed the recommended torque of 15 in/lbs on mounting screws.
- Always use blue Loctite on screws to prevent loosening during use.

• Age Warnings:

- This product is intended for use by individuals aged 18 and older.
- Keep this product out of reach of children.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is unloaded and safe to work on.
- Gather all necessary tools, including a 5/64" allen wrench.

2. Installation Steps:

- Remove the rear sight from your firearm.
- Install the EGW Sight Mount in the dovetail of your firearm.
- Tighten the set screw (if applicable).
- Place the red dot sight on the EGW Sight Mount.
 - Note: Placing a small piece of paper between the red dot sight and the sight mount will facilitate easier removal and protect the red dot sight from Loctite.
- Apply blue Loctite to the provided mounting screws.
- Torque the mounting screws to 15 in/lbs using the 5/64" allen wrench.

3. PostInstallation Check:

- Verify that all screws are secure and the sight is properly mounted.

- Conduct a function check to ensure the sight operates correctly.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Consider recycling options for metal components when possible.

Contact Information for Further Support

For any inquiries regarding safety or installation, please refer to the manufacturer's website or customer support resources.

Thank you for your attention to these safety instructions. Proper installation and care will ensure the optimal performance of your S&W Adjustable Rear Sight Trijicon RMR Sight Mount.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk