

MOUNT FOR AIMPOINT MICRO T-1 AND T-2 OPTIC - ARISAKA DEFENSE MOUNT FOR AIMPOINT MICRO T-1 & T-2 OPTIC, 1.93" HEIGHT, BLK

[Optics & Mounting](#) > [Electronic Sights](#) > [Mounting Hardware](#)

The Patent Pending Arisaka Low Aimpoint Micro Mount is designed for the Aimpoint Micro T1 and T2 optics, and will also function with other red dots using the same footprint, including the Aimpoint H1/H2, Aimpoint Comp M5/M5S, Aimpoint Duty, Sig Romeo 5, Vortex Crossfire, and Holosun HS503/515/530. The 0.9" optic centerline matches up with the Arisaka Low Magnifier Mounts, and is ideal for use on firearms like the IWI Galil Ace, SAN Swiss SG550/SG551/SG552/SG553, and AK platforms. Please note: the Aimpoint Comp M5S and Aimpoint Duty are 10mm taller than the regular Aimpoint Micro red dot sights, which must be factored into the final height of the optic, and will prevent them from lining up with the Arisaka Low Magnifier Mounts. Weight (including screws): 1.6 oz Optic Centerline: 0.9" with Aimpoint Micro T1/T2 Each mount is CNC machined from 6061-T651 and 7075-T651 aluminum and MIL-A-8625 Type III hard coat black anodized. Anodizing colors may slightly vary from part to part and batch to batch, and is completely normal. Includes all necessary screws and tools to attach optic to mount. Recommended torque values: Picatinny clamp - 50 inch lbs (5.7 Nm) Optic to mount - 11.9 inch lbs (1.35 Nm) Additional mounting details: the Aimpoint Micro mounting interface features three horizontal surfaces and two angled surfaces. The optic is supposed to contact the mount only on the angled surfaces, which wedges it into place and prevents the optic from changing zero under recoil or harsh handling. It is completely normal to see a tiny gap between the optic and horizontal surfaces of the mount. Hardware: One 10-32x1.25" torx socket cap screw, four M3x4mm torx button head screw. Made in the USA.

NO IMAGE
AVAILABLE

Attributes

- Name: [ARISAKA DEFENSE MOUNT FOR AIMPOINT MICRO T-1 & T-2 OPTIC, 1.93" HEIGHT, BLK](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 430104523
- Mfr. No.: OM-MICRO-193-BK
- Colour: Black
- Fits / Used For: Aimpoint Micro
- Height: 1.93"
- Weight: 0.1 lbs
- Delivery weight: 0.181kg
- Shipping height: 64mm
- Shipping width: 95mm
- Shipping length: 83mm
- UPC: 601557940216

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for Arisaka Defense Mount for Aimpoint Micro T1 and T2 Optic](#)
- [About Us](#)

Safety Instruction Guide for Arisaka Defense Mount for Aimpoint Micro T1 and T2 Optic

Introduction

Thank you for choosing the Arisaka Defense Mount for Aimpoint Micro T1 and T2 Optic. This guide provides important safety information, installation instructions, and usage guidelines to ensure safe and effective use of the product. Please read this guide carefully before using the mount.

General Safety Guidelines

- Ensure that the mount is compatible with your optic before installation.
- Always inspect the mount for any signs of damage or wear before each use.
- Keep the mount and optic out of reach of children and vulnerable individuals.
- Use the mount only as intended and according to the specifications outlined in this guide.
- Report any unsafe conditions or incidents to the appropriate authorities.
- Regularly check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- The mount is designed for use with the Aimpoint Micro T1 and T2 optics, as well as other compatible red dot sights. Ensure proper fit before use.
- Do not exceed the recommended torque values during installation:
 - Picatinny clamp: 50 inch lbs (5.7 Nm)
 - Optic to mount: 11.9 inch lbs (1.35 Nm)
- Ensure that the optic contacts only the angled surfaces of the mount. A small gap between the optic and the horizontal surfaces is normal.
- Avoid using the mount in extreme conditions that may affect its performance, such as exposure to excessive moisture or extreme temperatures.
- Regularly check the mounting screws for tightness to ensure secure attachment.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including the provided screws and a torque wrench.
- Ensure that the mounting surface is clean and free of debris.

2. Mounting the Optic:

- Align the optic with the mounting interface on the mount.
- Place the optic so that it contacts only the angled surfaces of the mount.
- Insert the provided screws into the appropriate holes and handtighten them.

3. Securing the Optic:

- Use a torque wrench to tighten the screws to the recommended torque values:
 - Picatinny clamp: 50 inch lbs (5.7 Nm)
 - Optic to mount: 11.9 inch lbs (1.35 Nm)

4. Final Inspection:

- Check that the optic is securely attached and that there are no visible gaps aside from the normal

- gap between the optic and horizontal surfaces.
- Conduct a function check to ensure the optic is properly aligned and operational.

5. Usage:

- Use the mount and optic in accordance with the manufacturer's guidelines.
- Avoid any modifications to the mount or optic that could compromise safety.

Disposal Instructions

- Dispose of the mount and any packaging materials in accordance with local regulations.
- Do not dispose of electronic components in regular household waste. Follow local electronic waste disposal guidelines.

Contact Information for Further Support

For any questions or concerns regarding the Arisaka Defense Mount for Aimpoint Micro T1 and T2 Optic, please refer to the manufacturer's website or contact their customer support for assistance.

By following these safety instructions, you can ensure the safe and effective use of your Arisaka Defense Mount for Aimpoint Micro T1 and T2 Optic. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk