

GRIDLOK 11" HANDGUARD FULL ASSEMBLY BLACK - GRIDLOK 11" HANDGUARD FULL ASSEMBLY IN BLACK

[Rifle Parts](#) > [Build Kits](#) > [Handguards & Rails](#)

Since the beginning, Strike Industries has constantly innovated and adapted to the needs of the modern shooter. Always striving to provide the best solutions and versatility when it comes to customization for the most popular firearm platforms. After 2 years of research and development, we are proud to announce the arrival of our GRIDLOK Handguard for the AR Platform. Our First Quick Detachable MLOK Handguard featuring full modular colorways with integrated backup sights, built in Picatinny mounts, and a spring loaded detach lever for the QUICKEST rail removal process ever. The GRIDLOK is precision CNC Milled from durable 6061 Aluminum, and given a semi-matte finish for the smoothest grip. The QD Locking Lever allows for rapid detachment of the rail housing from the barrel nut. Using 7250 Anodized Aluminum, the barrel nut creates a lightweight solution that is exclusive to the GRIDLOK system. The Gridlok also features the release of our new patented RaiLok mounting system. Combining the versatility of MLOK with the profile of a traditional picatinny, this rail attachment system is the best of both worlds, and allows for endless customization for accessory attachment and configurations. With a larger Internal diameter of 1.6" the GRIDLOK is built to accommodate mid to large compensators, namely the Strike Oppressor.



COMPATIBILITY: Mil-Spec M4 upper receiver **NOT COMPATIBLE:** Most piston gas blocks Some billet/side charging uppers **Torque:** 30-50 ft/lbs (47.45-67.79 nM) for the barrel nut *How to video available. The two locking screw at base can only be easily adjusted when the base is not mounted on barrel nut. *It is **NOT RECOMMEND** to adjust the locking tightness when you mount it on barrel nut. **Weight 11-Inch:** 15.38 oz **Product Features:** Quick rail detach, removing the rail housing from the barrel nut/ The QD Locking Lever features a tightness adjustment Barrel nut shroud and front rail (top & bottom) is modular and customizable/ New barrel nut material using 7250 Anodized aluminum vs. traditional steel. Integrated font sight/ Front top rail can be removed to accommodate A2 sight set-up RailLok (TM) can accommodate picatinny 1913 and MLOK accessories/ Integrated QD mount/ alignment set screws to center the rail on to the firearm platform Internal rail clearance is at 40.5mm - it will accommodate the Oppressor's Blast Shield **Package Includes:** 1X Handguard Main Housing 1X Top Rail 1X Bottom Rail 1X Barrel Nut Shroud 1X Set Of Tools 1X Enhanced Barrel Nut 1X Barrel Nut Tools 1X Warning card *It is **NOT RECOMMEND** to adjust the locking tightness when you mount it on barrel nut. **WARNING:** Before every use, always check proper function of your QD mount and any wear and tear from use Always have your weapon in the **SAFE** position when not being fired Always follow all firearms safety rules and never point your weapon at anything you are not willing to destroy -CALIFORNIA **PROPOSITION 65 WARNING:-** **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information: www.P65Warnings.ca.gov

Attributes

- Name: [GRIDLOK 11" HANDGUARD FULL ASSEMBLY IN BLACK](#)
- Manufacturer: [STRIKE INDUSTRIES](#)
- Product no.: 430105337

- Mfr. No.: SI-GRIDLOK-11-BK
- Color: Black
- Length: 11"
- Make: AR-15
- Style: Assembly
- Type: M-LOK
- Delivery weight: 0.672kg
- Shipping height: 330mm
- Shipping width: 76mm
- Shipping length: 70mm
- UPC: 708747548761

Item details

US export classification: 0A501.y.1

Table of Contents

- Startpage
- GRIDLOK 11" Handguard Full Assembly Safety Instruction Guide
- About Us

GRIDLOK 11" Handguard Full Assembly Safety Instruction Guide

Introduction

Thank you for choosing the GRIDLOK 11" Handguard Full Assembly in Black. This product is designed to enhance your firearm's functionality and customization. It is essential to follow the safety guidelines and instructions provided in this manual to ensure safe and effective use.

General Safety Guidelines

- Always handle your firearm with care and follow all firearms safety rules.
- Ensure that your weapon is in the SAFE position when not being fired.
- Before each use, check the proper function of your QD mount and inspect for any wear and tear.
- Never point your weapon at anything you are not willing to destroy.
- Be aware of your surroundings and ensure that you are in a safe environment when using your firearm.
- This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov.

Specific Safety Precautions for Use

- **Compatibility:** Ensure that the GRIDLOK Handguard is compatible with your firearm. It is designed for MilSpec M4 upper receivers and is not compatible with most piston gas blocks or some billet/side charging uppers.
- **Weight Limitations:** The weight of the 11inch handguard is 15.38 oz. Ensure that your firearm can support this weight without compromising performance.
- **Torque Settings:** Use a torque setting of 3050 ft/lbs (47.4567.79 nM) for the barrel nut. Adjustments to the locking screw at the base should only be made when the base is not mounted on the barrel nut.
- **Avoid Adjusting Under Load:** It is NOT RECOMMENDED to adjust the locking tightness when mounted on the barrel nut.

Instructions for Installation and Usage

Installation

1. Preparation:

- Ensure the firearm is unloaded and in a safe condition.
- Gather all necessary tools provided in the package.

2. Attach the Barrel Nut:

- Install the barrel nut onto the upper receiver, ensuring it is aligned correctly.
- Use the specified torque settings (3050 ft/lbs) to secure the barrel nut.

3. Install the Handguard:

- Slide the handguard over the barrel nut.
- Engage the QD Locking Lever to secure the handguard in place.

4. Adjust the Tightness:

- If necessary, adjust the tightness of the locking screw at the base of the handguard. Ensure this is done while the base is not mounted on the barrel nut.

5. Final Check:

- Inspect all connections and ensure that the handguard is securely attached.
- Verify that the integrated backup sights and Picatinny mounts are correctly positioned.

Usage

- Utilize the integrated QD mount for easy attachment and detachment of accessories.
- The RailLok system allows for the use of both picatinny 1913 and MLOK accessories, providing versatility for your configuration.
- Ensure that all accessories are securely attached before use.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste. Check with local waste management for proper disposal methods for aluminum and other materials.

Contact Information for Further Support

- For questions or concerns regarding the GRIDLOK Handguard, please refer to the manufacturer's website or contact the customer support team directly.

By following these safety instructions and guidelines, you can ensure a safe and effective experience with your GRIDLOK 11" Handguard Full Assembly. Thank you for your attention to safety, and enjoy your enhanced firearm experience.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at