

AK-47 DETENT AND SPRING - JMAC CUSTOMS GBC-13 - DETENT AND SPRING

[Gunsmith Tools](#) > [Rifle Tools](#) > [Gas System Tools](#)

AK-47 detent and spring for installing the front sight block.



Attributes

- Name: [JMAC CUSTOMS GBC-13 - DETENT AND SPRING](#)
- Manufacturer: [JMAC CUSTOMS](#)
- Product no.: 430106328
- Mfr. No.: B4-51
- Weapon type: AK-47
- Shipping height: 76mm
- Shipping width: 76mm
- Shipping length: 76mm

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for AK47 Detent and Spring JMAC Customs GBC13
- About Us

Safety Instruction Guide for AK47 Detent and Spring JMAC Customs GBC13

Introduction

Thank you for choosing the AK47 Detent and Spring from JMAC Customs. This product is designed for the installation of the front sight block on your AK47. It is essential to follow these safety guidelines to ensure a safe and effective use of this product. This guide complies with the EU General Product Safety Regulation (GPSR) to help protect consumers.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Keep the product out of reach of children and vulnerable individuals.
- Always inspect the product for any damage before use. Do not use if damaged.
- Use appropriate safety gear, such as safety glasses and gloves, during installation.
- Report any unsafe products or accidents to the relevant authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Only use this detent and spring with compatible AK47 models.
- Ensure that the firearm is unloaded before starting the installation process.
- Avoid using excessive force during installation to prevent damage to components.
- Be cautious of sharp edges and small parts that may pose a choking hazard.
- Follow all local laws and regulations regarding firearm modifications.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is completely unloaded and safe to handle.
- Gather necessary tools: a punch tool, hammer, and appropriate safety gear.

2. Installation Steps:

- Locate the front sight block on your AK47.
- Carefully remove the existing detent and spring if applicable.
- Insert the new detent into the designated hole of the front sight block.
- Place the spring into position, ensuring it is properly seated.
- Use the punch tool to gently press the detent into place, ensuring a secure fit.
- Doublecheck the installation to confirm that the detent and spring are properly aligned.

3. Post Installation:

- Inspect the installation to ensure everything is secure and functioning correctly.
- Test the front sight block to confirm proper operation.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste disposal regulations.
- If the product becomes damaged or is no longer in use, dispose of it responsibly, ensuring that it does not pose a risk to the environment or public safety.

Contact Information for Further Support

For any inquiries regarding safety or product information, please refer to the official website of the manufacturer or consult your local authorities for further assistance.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk