

B.A. SLING POINT FOR RUGER® MINI-14® & RUGER® MINI THIRTY® - SAMSON MANUFACTURING CORP B.A. SLING POINT FOR RUGER MINI-14 & THIRTY 2008/LATER BLACK

[Shooting Accessories](#) > [Slings & Sling Swivels](#) > [Tactical Sling Mounts](#)

Upgrade your factory gas block with their original B.A. Sling Point gas block cap designed for the Ruger® Mini-14® and Mini Thirty® 2008 or later in Black or Stainless are compatible with Mini-14® rifles with a factory flanged .625"" diameter barrel manufactured in 2008 or later, with a serial number prefix of 508 or higher. Additionally, Mini Thirty® rifles with the older factory straight pencil .625"" diameter barrel and the new factory flanged .625"" diameter barrel will be compatible. 2007 or earlier in Black or Stainless are compatible with Mini-14® rifles with a factory straight pencil .562"" diameter barrel manufactured in 2007 or earlier, with a serial number prefix of 181 through 199, but not including 580 or higher. B.A. Sling Point Features: Replaces the factory Ruger® Mini-14® or Mini Thirty® gas block cap Integrated sling attachment point It's BadAss Specifications: Material: 303 Stainless Steel / 4140 Chromoly Steel Finish: Stainless or Black Oxide Length: 1.25" Width: 1.75" Height: .5" Weight: 1.3 oz.



Attributes

- Name: [SAMSON MANUFACTURING CORP B.A. SLING POINT FOR RUGER MINI-14 & THIRTY 2008/LATER BLACK](#)
- Manufacturer: [SAMSON MANUFACTURING CORP](#)
- Product no.: 430107475
- Mfr. No.: 04-06102-03
- Colour: Black
- Delivery weight: 0.037kg
- Shipping height: 127mm
- Shipping width: 133mm
- Shipping length: 38mm
- UPC: 850028390863

Item details

Made in USA

Table of Contents

- Startpage
- B.A. Sling Point for Ruger® Mini14® & Mini Thirty® Safety Instruction Guide
- About Us

B.A. Sling Point for Ruger® Mini14® & Mini Thirty® Safety Instruction Guide

Introduction

Thank you for choosing the B.A. Sling Point for your Ruger® Mini14® or Mini Thirty®. This guide provides important safety instructions, installation procedures, and maintenance tips to ensure safe and effective use of the product. Please read this guide carefully before installation and usage.

General Safety Guidelines

- Ensure that the product is compatible with your Ruger® Mini14® or Mini Thirty® model based on the specifications provided.
- Always handle firearms in a safe manner and follow all firearm safety rules.
- Keep the product and all related tools out of reach of children and unauthorized users.
- Inspect the product regularly for any signs of wear or damage.
- If you notice any defects or if the product does not function as intended, discontinue use immediately and seek assistance.

Specific Safety Precautions for Use

- **Compatibility Check:** Ensure that your Ruger® Mini14® or Mini Thirty® model is manufactured in 2008 or later and has a factory flanged .625" diameter barrel. Older models may not be compatible and could pose safety risks.
- **Installation Area:** Perform installation in a clean, welllit, and dry area to avoid losing small parts.
- **Sling Attachment:** When using the sling attachment point, ensure that the sling is securely fastened to prevent accidental detachment during use.
- **Weight Limit:** Do not exceed the recommended weight limit for the sling attachment to prevent failure.
- **Regular Inspection:** Periodically check the integrity of the sling point and surrounding areas to ensure they remain secure and functional.

Instructions for Installation and Usage

1. **Gather Required Tools:** You will need a suitable wrench or tool for installation, as well as a clean workspace.
2. **Remove Existing Gas Block Cap:**
 - Ensure the firearm is unloaded and pointed in a safe direction.
 - Carefully remove the existing gas block cap from your Ruger® Mini14® or Mini Thirty®.
3. **Install the B.A. Sling Point:**
 - Align the B.A. Sling Point with the gas block area.
 - Securely fasten it in place, ensuring it is tightly fitted to avoid any movement during use.
4. **Attach Sling:**
 - Once installed, attach your sling to the integrated sling attachment point.
 - Ensure that the sling is properly secured and tested for stability before use.
5. **Final Check:**
 - Verify that all components are installed correctly and that there are no loose parts.
 - Conduct a function check to ensure proper operation before heading to the range or field.

Disposal Instructions

- Dispose of the B.A. Sling Point and any packaging materials in accordance with local regulations.
- Do not dispose of the product in regular household waste if it is damaged or defective.
- Consider recycling materials where possible, particularly metal components.

Contact Information for Further Support

For any safety inquiries or further assistance, please consult the manufacturer's website or customer service resources. It is essential to follow all guidelines and ensure safe handling of your product.

By following these instructions and guidelines, you can ensure a safe and effective experience with your B.A. Sling Point for Ruger® Mini14® & Mini Thirty®. Always prioritize safety and responsible firearm handling practices.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk