

# **EXOS-513 PISTOL COMPENSATOR FOR GLOCK® GEN-3 17/19/34 & FX-19 - FAXON FIREARMS EXOS-513 PISTOL COMPENSATOR FOR GEN-3 GLOCK 17/19/34 & FX-19**

[Handgun Parts](#) > [Barrel Parts](#) > [Muzzle Devices](#) > [Compensators](#)

Faxon Firearms compensators are designed for Glock Gen 3 and Faxon Firearms FX-19 pistols. Fitment with other pistols or generations cannot be guaranteed. Testing for fit and function was performed on these models specifically: Glock 19 Gen 3 Glock 17 Gen 3 Glock 34 Gen 3 Faxon Firearms FX-19 Hellfire Constructed of 6061 Aluminum with a black anodized finish, Faxon Pistol Compensators feature a uniquely angled front port single chamber design, enabling the compensator to improve consistency while reducing muzzle climb and recoil. The angled ports allow gas to deflect upwards as opposed to only deflecting sideways, reducing up and down muzzle movement and improving reliability. Barrel protrusion is designed to fit flush with the slide and has been optimized for Faxon branded barrels. For all other barrels, the barrel should protrude .600" or less for a flush fit. Each compensator comes complete with thread locker, two 6-32 set screws, and a 1/16 Allen wrench. SPECS Length: 1.1in Width: 1in Height: 1.2in Weight: .06lbs Thread: 1/2x28 Caliber: 9mm \*Compensators can affect the timing of your pistol and may require adjustments in lubrication, ammunition, and other areas. DISCLAIMER: "GLOCK" is a federally registered trademark of GLOCK, Inc. and is one of many trademarks owned by GLOCK, Inc. or GLOCK Ges.m.b.H. Neither Brownells nor this site are affiliated in any manner with, or otherwise endorsed by, GLOCK, Inc. or GLOCK Ges.m.b.H. The use of "GLOCK" on this page is merely to advertise the sale of GLOCK pistols, parts, or components. For genuine GLOCK, Inc. and GLOCK Ges.m.b.H. products and parts visit [www.glock.com](http://www.glock.com)."



## **Attributes**

- Name: [FAXON FIREARMS EXOS-513 PISTOL COMPENSATOR FOR GEN-3 GLOCK 17/19/34 & FX-19](#)
- Manufacturer: [FAXON FIREARMS](#)
- Product no.: 430108207
- Mfr. No.: FF-P-A-COMP-DS-G-01
- Weapon type: Glock
- Delivery weight: 0.054kg
- Shipping height: 160mm
- Shipping width: 38mm
- Shipping length: 89mm
- UPC: 816341026179

## **Item details**

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for EXOS513 Pistol Compensator for Glock® Gen3 17/19/34 & FX19
- About Us

# Safety Instruction Guide for EXOS513 Pistol Compensator for Glock® Gen3 17/19/34 & FX19

## Introduction

Thank you for choosing the EXOS513 Pistol Compensator designed for Glock® Gen3 models 17, 19, 34, and Faxon Firearms FX19. This guide provides essential safety information and instructions to ensure proper use and maintenance of the product. Please read this document carefully to maximize safety and performance.

## General Safety Guidelines

- Always treat your firearm and its components with respect and care.
- Ensure that the compensator is compatible with your specific model before installation.
- Follow all local laws and regulations regarding firearm modifications.
- Store the compensator and firearm securely to prevent unauthorized access.
- Use only recommended ammunition and ensure proper lubrication for optimal performance.
- Regularly inspect the compensator for any signs of wear or damage.

## Specific Safety Precautions for Use

- The EXOS513 Pistol Compensator is designed for use with Glock Gen 3 and Faxon Firearms FX19 pistols only. Using it with other models may pose safety risks.
- Ensure that the barrel protrusion is .600 inches or less for a flush fit; improper fit can affect firearm performance and safety.
- Be aware that compensators can affect the timing of your pistol, which may require adjustments in lubrication, ammunition, and other areas.
- Always wear appropriate eye and ear protection when firing your firearm.
- Keep the firearm pointed in a safe direction at all times during installation and use.

## Instructions for Installation and Usage

### 1. Preparation:

- Ensure that your firearm is unloaded and pointed in a safe direction.
- Gather the necessary tools: thread locker, two 632 set screws, and a 1/16 Allen wrench.

### 2. Installation Steps:

- Remove the existing muzzle device from the firearm's barrel.
- Clean the barrel threads to remove any debris or residue.
- Apply a small amount of thread locker to the threads of the compensator.
- Screw the compensator onto the barrel, ensuring it is securely fastened.
- Use the 1/16 Allen wrench to tighten the two set screws against the barrel for added stability.
- Check that the compensator fits flush with the slide.

### 3. Usage:

- Before firing, ensure that all components are securely installed and that the firearm is in proper working condition.
- Fire the firearm in a controlled environment, observing all safety protocols.
- Monitor the compensator for any signs of loosening or damage during use.

## Disposal Instructions

- Dispose of the EXOS513 Pistol Compensator in accordance with local regulations regarding firearm components.
- Do not dispose of the compensator in regular household waste; contact local waste management authorities for proper disposal methods.

## Contact Information for Further Support

For any inquiries or concerns regarding the EXOS513 Pistol Compensator, please reach out to your retailer or manufacturer directly. Ensure you have your product details on hand for efficient assistance.

## Conclusion

By following these safety instructions and guidelines, you can ensure a safe and enjoyable experience with your EXOS513 Pistol Compensator. Always prioritize safety and compliance with local laws when using firearm accessories. Thank you for your attention to safety and responsible firearm use.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)