

EXOS-533 PISTOL COMPENSATOR FOR GLOCK® 43X/48 - FAXON FIREARMS EXOS-533 PISTOL COMPENSATOR FOR GLOCK 43X/48 BLACK

[Handgun Parts](#) > [Barrel Parts](#) > [Muzzle Devices](#) > [Compensators](#)

Faxon Firearms Pistol Compensators have been tested and confirmed compatible with Glock® 43X and Glock® 48 Pistols. Constructed of 6061 aluminum with a black anodized finish, Faxon Pistol Compensators feature a uniquely angled front port single chamber design, enabling the compensator to improve consistency while reducing muzzle climb and recoil. The angled ports allow gas to deflect upwards as opposed to only deflecting sideways, reducing up and down muzzle movement and improving reliability. Barrel protrusion is designed to fit flush with the slide and has been optimized for Faxon branded barrels. For all other barrels, the barrel should protrude .600" or less for a flush fit. Each compensator comes complete with thread locker, two 6-32 set screws, and a 1/16 Allen wrench. SPECS Length: 1.218" Width: .865" Height: 1.269" Weight: .05lbs Thread: 1/2"x28 Caliber: 9mm



*Compensators can affect the timing of your pistol and may require adjustments in lubrication, ammunition, and other areas. DISCLAIMER: "GLOCK" is a federally registered trademark of GLOCK, Inc. and is one of many trademarks owned by GLOCK, Inc. or GLOCK Ges.m.b.H. Neither Brownells nor this site are affiliated in any manner with, or otherwise endorsed by, GLOCK, Inc. or GLOCK Ges.m.b.H. The use of "GLOCK" on this page is merely to advertise the sale of GLOCK pistols, parts, or components. For genuine GLOCK, Inc. and GLOCK Ges.m.b.H. products and parts visit www.glock.com."

Attributes

- Name: [FAXON FIREARMS EXOS-533 PISTOL COMPENSATOR FOR GLOCK 43X/48 BLACK](#)
- Manufacturer: [FAXON FIREARMS](#)
- Product no.: 430108209
- Mfr. No.: FF-P-A-COMP-SS-G-02
- Model: 48,43X
- Weapon type: Glock
- Delivery weight: 0.054kg
- Shipping height: 160mm
- Shipping width: 38mm
- Shipping length: 89mm
- UPC: 816341026445

Item details

Made in USA

Table of Contents

- Startpage
- EXOS533 Pistol Compensator Safety Instructions
- About Us

EXOS533 Pistol Compensator Safety Instructions

Introduction

Thank you for choosing the EXOS533 Pistol Compensator for your Glock® 43X/48. This guide provides essential safety information and instructions to ensure the proper and safe use of the product. Please read this guide carefully before installation and use.

General Safety Guidelines

- Product Safety: Ensure that the EXOS533 Pistol Compensator is used only with Glock® 43X and Glock® 48 pistols. Using it with other firearms may pose risks.
- Enhanced Recalls: Stay informed about any recalls related to the product. Check the manufacturer's website for updates.
- Online Shopping: Ensure you purchase the compensator from a reputable source to guarantee product authenticity and safety.
- Special Consumer Focus: This product is designed for adult users. Keep it out of reach of children and vulnerable individuals.
- EU Contact Point: For safety inquiries, please refer to the manufacturer's official website or customer service.
- Rapid Alerts: Be aware of any notifications regarding unsafe products through the EU's Safety Gate system.

Specific Safety Precautions for Use

- Always ensure the firearm is unloaded before installing or adjusting the compensator.
- Verify that the barrel protrudes .600" or less for a flush fit with the compensator.
- Use the provided thread locker to secure the compensator properly.
- Do not exceed the recommended ammunition specifications, as this may affect performance and safety.
- Regularly inspect the compensator for signs of wear or damage. Replace if necessary.
- Ensure that the compensator is properly installed before use to avoid malfunctions.
- Be cautious of the compensator's effects on muzzle rise and recoil; practice accordingly.

Instructions for Installation and Usage

1. Preparation:

- Ensure your Glock® 43X or 48 is unloaded.
- Gather the necessary tools: a 1/16 Allen wrench (included) and thread locker (included).

2. Installation:

- Remove the existing muzzle device if applicable.
- Apply thread locker to the threads of the compensator.
- Screw the compensator onto the barrel until it is snug.
- Use the 632 set screws to secure the compensator in place. Tighten them using the Allen wrench.
- Check that the barrel protrudes .600" or less for a proper fit.

3. Usage:

- After installation, check the compensator for stability.
- Test fire the pistol in a safe environment to ensure proper function.
- Monitor the performance of the compensator and make adjustments as necessary.

Disposal Instructions

- Dispose of the EXOS533 Pistol Compensator in accordance with local regulations.
- Do not discard in regular household waste. Check with local waste management for proper disposal methods.

Contact Information for Further Support

For further assistance, please refer to the manufacturer's official website or customer service for inquiries related to safety, installation, or product performance.

By following these safety instructions, you can ensure a safer and more enjoyable experience with your EXOS533 Pistol Compensator. Always prioritize safety and responsible firearm use.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk