

EXOS-553 PISTOL COMPENSATOR FOR GLOCK® GEN-5 17/19/34 - FAXON FIREARMS EXOS-553 PISTOL COMPENSATOR FOR GEN-5 GLOCK 17/19/34

[Handgun Parts](#) > [Barrel Parts](#) > [Muzzle Devices](#) > [Compensators](#)

Faxon Firearms EXOS-553 compensators are designed for Glock® Gen 5 9mm pistols. Fitment with other pistols or generations cannot be guaranteed.

Testing for fit and function was performed on these models specifically: Glock 19 Gen 5 Glock 17 Gen 5 Glock 34 Gen 5 Constructed of 6061 Aluminum with a black anodized finish, Faxon Pistol Compensators feature a uniquely angled front port single chamber design, enabling the compensator to improve consistency while reducing muzzle climb and recoil. The angled ports allow gas to deflect upwards as opposed to only deflecting sideways, reducing up and down muzzle movement and improving reliability. Barrel protrusion is designed to fit flush with the slide and has been optimized for Faxon branded barrels. For all other barrels, the barrel should protrude .600" or less for a flush fit. Each compensator comes complete with thread locker, two 6-32 set screws, and a 1/16 Allen wrench. SPECS Length: 1.299" Width: 1" Height: 1.271" Weight: .06lbs Thread: 1/2x28 Caliber: 9mm *Compensators can affect the timing of your pistol and may require adjustments in lubrication, ammunition, and other areas. DISCLAIMER: "GLOCK" is a federally registered trademark of GLOCK, Inc. and is one of many trademarks owned by GLOCK, Inc. or GLOCK Ges.m.b.H. Neither Brownells nor this site are affiliated in any manner with, or otherwise endorsed by, GLOCK, Inc. or GLOCK Ges.m.b.H. The use of "GLOCK" on this page is merely to advertise the sale of GLOCK pistols, parts, or components. For genuine GLOCK, Inc. and GLOCK Ges.m.b.H. products and parts visit www.glock.com."



Attributes

- Name: [FAXON FIREARMS EXOS-553 PISTOL COMPENSATOR FOR GEN-5 GLOCK 17/19/34](#)
- Manufacturer: [FAXON FIREARMS](#)
- Product no.: 430108211
- Mfr. No.: FF-P-A-COMP-DS-G-03
- Model: Gen 5
- Weapon type: Glock
- Delivery weight: 0.054kg
- Shipping height: 160mm
- Shipping width: 38mm
- Shipping length: 89mm
- UPC: 816341026469

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for EXOS553 Pistol Compensator
- About Us

Safety Instruction Guide for EXOS553 Pistol Compensator

Introduction

Thank you for choosing the Faxon Firearms EXOS553 Pistol Compensator. This product is designed specifically for Glock® Gen 5 9mm pistols, including models 17, 19, and 34. This guide provides important safety instructions, installation guidelines, and disposal information to ensure safe and effective use of the compensator.

General Safety Guidelines

- Ensure that the compensator is compatible with your specific pistol model. This product is designed for Glock® Gen 5 only.
- Always handle firearms and accessories responsibly and in accordance with local laws and regulations.
- Inspect the compensator for any damage or defects before installation. Do not use if damaged.
- Keep the product out of reach of children and unauthorized users.
- Use appropriate personal protective equipment (PPE) when handling firearms, including eye and ear protection.
- Be aware of your surroundings and ensure a safe shooting environment when using your pistol.

Specific Safety Precautions for Use

- The use of compensators can affect the timing of your pistol. Be prepared to make necessary adjustments to lubrication, ammunition, and shooting technique.
- Ensure that the barrel protrudes .600 inches or less for a flush fit with the compensator.
- Regularly check the tightness of the set screws after installation and before each use.
- Avoid using the compensator with other brands or models of pistols unless compatibility is confirmed.
- Do not attempt to modify or disassemble the compensator. Unauthorized modifications may lead to unsafe conditions.

Instructions for Installation and Usage

1. Installation

- Ensure the pistol is unloaded and pointed in a safe direction.
- Clean the threaded area of the barrel to remove any debris or oil.
- Apply thread locker to the threads of the compensator.
- Screw the compensator onto the barrel until it is handtight.
- Use the included 1/16 Allen wrench to tighten the two 632 set screws securely against the barrel.
- Check that the compensator is flush with the slide and that the barrel protrusion is within specifications.

2. Usage

- Before firing, ensure that the compensator is securely attached and that all components are functioning properly.
- When firing, maintain a firm grip on the pistol to control recoil effectively.
- Monitor the performance of the compensator during use. If you notice any unusual behavior, stop using the pistol and inspect the compensator.
- After use, clean the compensator to prevent buildup of residue.

Disposal Instructions

- Dispose of the product in accordance with local regulations for metal and aluminum waste.
- Do not dispose of the compensator in regular household waste. Check with local waste management authorities for proper disposal methods.

Contact Information for Further Support

For any safety inquiries or support related to the Faxon Firearms EXOS553 Pistol Compensator, please refer to the official Faxon Firearms website or contact your local authorized dealer.

Disclaimer: This safety instruction guide does not replace the need for proper training in firearm safety and handling. Always seek professional instruction and adhere to local laws and regulations when using firearms and accessories.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk