

HOST RING SIGHTS FOR HENRY - XS SIGHT SYSTEMS HENRY HOST RING SIGHT SET .357 CALIBER WITH RAMP

[Rifle Parts](#) > [Sights](#) > [Sight Sets](#)

The XS Ghost Ring WS hunting sights pairs with XS Lever Rail HN-6000R-N to offer improved accuracy and faster sight acquisition in a rugged all-steel design. Fits Henry .357 with round barrel and screw on front sight. Does not fit models with front sight blade dovetailed directly into the barrel. Precision machined in Fort Worth, TX. XS Ghost Ring WS is fully adjustable for windage and elevation and comes with two apertures, .230" and .191" inside diameter, for different lighting conditions. The large Ghost Ring affords great field of view for fast target acquisition. The XS White Stripe (WS) front sight replaces the existing blade and ramp and features a blued steel body with a painted white stripe face. White on black front post is highly visible in all lighting conditions, as well as provides contrast against any color background. Due to moving the rear sight from the barrel to the receiver, some zeroing issues might arise. Alternate front sight heights are available and covered under XS' No Questions Asked Warranty. For use with Lever Rail only.



Attributes

- Name: [XS SIGHT SYSTEMS HENRY GHOST RING SIGHT SET .357 CALIBER WITH RAMP](#)
- Manufacturer: [XS SIGHT SYSTEMS](#)
- Product no.: 430109197
- Mfr. No.: HN-0003-5
- Colour: Black
- Model: Big Boy
- Style: Ghost Ring
- Weapon type: Henry
- Delivery weight: 0.095kg
- Shipping height: 32mm
- Shipping width: 127mm
- Shipping length: 210mm
- UPC: 647533001236

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for GHOST RING SIGHTS FOR HENRY XS SIGHT SYSTEMS
- About Us

Safety Instruction Guide for GHOST RING SIGHTS FOR HENRY XS SIGHT SYSTEMS

Introduction

Thank you for choosing the GHOST RING SIGHTS FOR HENRY XS SIGHT SYSTEMS. This product is designed to enhance your shooting experience by providing improved accuracy and faster sight acquisition. To ensure your safety and the optimal performance of your sight system, please read and follow the guidelines outlined in this document.

General Safety Guidelines

- Always treat your firearm and its accessories as if they are loaded.
- Ensure that you are in a safe environment when handling or installing your ghost ring sights.
- Use the product only for its intended purpose as described in this guide.
- Keep the sight system out of the reach of children and unauthorized users.
- Regularly inspect your sight for any signs of wear or damage before each use.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform to stay informed.

Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before attempting to install or adjust the sights.
- Use the correct tools as specified in the installation instructions to prevent damage.
- Be aware of your surroundings and ensure a clear line of sight when aiming.
- Avoid using the sight system in adverse weather conditions that may impair visibility.
- If you experience any issues with zeroing the sight, consult the installation instructions or seek professional assistance.
- Be cautious when adjusting the windage and elevation settings to avoid misalignment.

Instructions for Installation and Usage

Installation Instructions

1. Preparation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools: a screwdriver and any other specific tools mentioned in the installation instructions.

2. Removing the Existing Sight:

- Carefully remove the existing front sight blade using the appropriate tool.
- Store the removed sight in a safe place for potential future use.

3. Installing the Ghost Ring Sight:

- Align the new XS Ghost Ring WS with the mounting location on the firearm.
- Secure the sight using the screws provided in the kit. Ensure that it is tightened properly but avoid overtightening.

4. Adjusting for Windage and Elevation:

- Use the provided apertures (.230" and .191" inside diameter) according to your lighting conditions.

- Adjust the windage and elevation settings as needed for optimal accuracy.

5. Final Inspection:

- Doublecheck all screws and adjustments to ensure everything is secure.
- Conduct a function check to verify that the sight is operating correctly.

Usage Instructions

- Use the XS Ghost Ring WS in conjunction with the XS Lever Rail HN6000RN for best performance.
- Familiarize yourself with the sight's features and adjustments before heading to the range.
- Practice target acquisition in a controlled environment to build confidence and proficiency.

Disposal Instructions

- Dispose of packaging materials responsibly, following local recycling guidelines.
- If the product is damaged beyond repair, dispose of it in accordance with local regulations for electronic waste and firearms accessories.

Contact Information for Further Support

For any questions, concerns, or additional support regarding your GHOST RING SIGHTS FOR HENRY XS SIGHT SYSTEMS, please refer to the manufacturer's website or customer service resources.

Thank you for your attention to these safety instructions. Enjoy your enhanced shooting experience with the GHOST RING SIGHTS!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk