

OPTIC MOUNT FOR HENRY - XS SIGHT SYSTEMS HENRY OPTIC MOUNTING RAIL FOR HENRY 45-70 CALIBER

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The XS Lever Rail upgrades the Henry .357 to allow for mounting of an optic in multiple positions. Fits Henry Steel Frame, Big Boy, round barrel carbines chambered in .357 Mag. (Does not fit Big Boy .357 Mag X Carbines.)

Lightweight, anodized aluminum rail is machined to Picatinny specs and allows scope mounting directly over the receiver, or forward for scout scopes or red dot sights. Installation requires removal of factory rear sight. All screws torque to 20 INCH-pounds; over-torquing can fracture or break screws. The XS Sights Lever Rail will not work on Henry rifles with brass receivers or octagonal barrels. The rail can not be modified to work on them. The XS Sights Lever Rail will not work, nor can it be modified to work, on Henry rifles chambered in .30-30.



Attributes

- Name: [XS SIGHT SYSTEMS HENRY OPTIC MOUNTING RAIL FOR HENRY 45-70 CALIBER](#)
- Manufacturer: [XS SIGHT SYSTEMS](#)
- Product no.: 430109204
- Mfr. No.: HN-6000R-N
- Colour: Black
- Material: Aluminum
- Model: 45/70
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Henry
- Delivery weight: 0.181kg
- Shipping height: 356mm
- Shipping width: 44mm
- Shipping length: 44mm
- UPC: 647533007979

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for OPTIC MOUNT FOR HENRY XS SIGHT SYSTEMS
- About Us

Safety Instruction Guide for OPTIC MOUNT FOR HENRY XS SIGHT SYSTEMS

Introduction

Thank you for choosing the OPTIC MOUNT FOR HENRY XS SIGHT SYSTEMS. This guide provides essential safety information and instructions to ensure proper use and installation of the product. Please read this guide carefully before use to maximize safety and performance.

General Safety Guidelines

- Ensure that the optic mount is compatible with your specific Henry rifle model before installation.
- Always handle firearms and accessories responsibly and in accordance with local laws and regulations.
- Keep the optic mount and all related components out of reach of children and unauthorized users.
- Regularly inspect the optic mount for signs of wear or damage before use.
- If you notice any defects or damages, discontinue use immediately and consult a qualified professional.

Specific Safety Precautions for Use

- Only use the XS Sights Lever Rail with Henry rifles that have steel frames and round barrels chambered in .357 Mag.
- Do not attempt to modify the rail for use with brass receivers, octagonal barrels, or .3030 chambered rifles.
- Ensure all screws are torqued to 20 INCHpounds as specified. Overtorquing can lead to fractures or breakage of screws.
- Always use appropriate tools for installation to avoid damage to the optic mount or rifle.
- Avoid using the optic mount in extreme environmental conditions that may affect its performance.

Instructions for Installation and Usage

1. Preparation

- Gather necessary tools: a torque wrench and appropriate screwdrivers.
- Ensure the rifle is unloaded and in a safe position before beginning installation.

2. Remove Factory Rear Sight

- Carefully remove the factory rear sight from your Henry rifle, following manufacturer instructions.

3. Install the XS Sights Lever Rail

- Align the XS Sights Lever Rail with the mounting holes on the receiver of the rifle.
- Insert screws through the rail into the receiver holes.

4. Torque the Screws

- Using a torque wrench, tighten all screws to a torque of 20 INCHpounds.
- Ensure that screws are evenly tightened to avoid misalignment or damage.

5. Mount the Optic

- Follow the manufacturer's instructions for mounting your optic onto the rail.
- Ensure the optic is securely fastened and properly aligned.

6. Final Inspection

- Inspect the installation to ensure everything is secure and properly aligned.
- Perform a function check of the rifle to ensure proper operation.

Disposal Instructions

- Dispose of any packaging materials in accordance with local recycling regulations.
- If the optic mount becomes damaged beyond repair, dispose of it responsibly to minimize environmental impact.

Contact Information for Further Support

For any safety inquiries or concerns regarding the OPTIC MOUNT FOR HENRY XS SIGHT SYSTEMS, please refer to the manufacturer or authorized dealer for assistance.

Thank you for prioritizing safety and compliance with these guidelines. Enjoy your shooting experience with the OPTIC MOUNT FOR HENRY XS SIGHT SYSTEMS!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk