

# OPTIC MOUNT & GHOST RING SIGHT SET FOR ROSSI 95 - XS SIGHT SYSTEMS OPTIC MOUNTING RAIL & GHOST RING SIGHT SET FOR ROSSI

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The XS Lever Rail Ghost Ring WS upgrades the Rossi R95 in .30-30 to allow for mounting of an optic in multiple positions and adds rugged all-steel back up iron sights. Fits Rossi R95 in .30-30 with round barrel and existing front sight blade and ramp that is screwed onto the barrel. Lightweight, anodized aluminum rail is machined to Picatinny specs and allows scope mounting directly over the receiver, or forward for scout scopes or red dot sights. XS Ghost Ring WS is fully adjustable for windage and elevation and comes with two apertures, .230" and .191" inside diameter, for different lighting conditions. The large Ghost Ring affords great field of view for fast target acquisition. The XS White Stripe (WS) front sight replaces the existing blade and ramp and features a blued steel body with a painted white stripe face. White on black front post is highly visible in all lighting conditions, as well as provides contrast against any color background. Due to moving the rear sight from the barrel to the receiver, some zeroing issues might arise. Alternate front sight heights are available and covered under XS' No Questions Asked Warranty. Installation requires removal of factory rear sight. All screws torque to 20 INCH-pounds; over-torqueing can fracture or break screws.



## Attributes

- Name: [XS SIGHT SYSTEMS OPTIC MOUNTING RAIL & GHOST RING SIGHT SET FOR ROSSI](#)
- Manufacturer: [XS SIGHT SYSTEMS](#)
- Product no.: 430109205
- Mfr. No.: TS-1001-5
- Colour: Black
- Material: Aluminum
- Model: R95
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Rossi
- Delivery weight: 0.227kg
- Shipping height: 51mm
- Shipping width: 51mm
- Shipping length: 356mm
- UPC: 647533001069

## Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for OPTIC MOUNT & GHOST RING SIGHT SET FOR ROSSI 95 XS SIGHT SYSTEMS
- About Us

# Safety Instruction Guide for OPTIC MOUNT & GHOST RING SIGHT SET FOR ROSSI 95 XS SIGHT SYSTEMS

## Introduction

Thank you for choosing the OPTIC MOUNT & GHOST RING SIGHT SET FOR ROSSI 95 XS SIGHT SYSTEMS. This product is designed to enhance your shooting experience by allowing for the mounting of optics and providing improved sighting options. It is important to read and understand these safety instructions to ensure safe and effective use of the product.

## General Safety Guidelines

- Ensure that the product is installed according to the instructions provided in this guide.
- Always handle firearms with care and follow all safety protocols.
- Keep this product out of reach of children and unauthorized users.
- Regularly inspect the product for any signs of wear or damage.
- If you experience any issues with the product, discontinue use immediately and seek assistance.

## Specific Safety Precautions for Use

- **Installation Precautions:**
  - Ensure that the firearm is unloaded before starting the installation process.
  - Use proper tools to avoid damaging the product or the firearm.
- **Usage Precautions:**
  - Always use eye protection when using firearms equipped with this product.
  - Be aware of your surroundings and ensure a safe shooting environment.
  - Do not exceed the recommended torque specifications when securing screws (20 INCHpounds).
- **Zeroing Issues:**
  - Be prepared for potential zeroing issues due to the relocation of the rear sight. Make adjustments as necessary.
- **Vulnerable Users:**
  - This product is not intended for use by individuals under the age of 18 without adult supervision.

## Instructions for Installation and Usage

1. **Preparation:**
  - Ensure the firearm is unloaded and in a safe condition.
  - Gather necessary tools, including a torque wrench.
2. **Removal of Existing Rear Sight:**
  - Carefully remove the factory rear sight from the firearm.
3. **Installation of the XS Lever Rail:**
  - Align the XS Lever Rail with the receiver and secure it using the provided screws.
  - Torque screws to 20 INCHpounds. Avoid overtorqueing to prevent damage.
4. **Installation of the Ghost Ring Sight:**
  - Attach the Ghost Ring Sight to the XS Lever Rail.
  - Adjust for windage and elevation as needed.
5. **Front Sight Replacement:**
  - Remove the existing front sight blade and ramp.
  - Install the XS White Stripe (WS) front sight, ensuring it is securely in place.
6. **Final Checks:**
  - Inspect all connections to ensure they are secure.

- Perform a function check on the firearm to ensure proper operation.

## Disposal Instructions

- Dispose of packaging materials responsibly and in accordance with local regulations.
- If the product is no longer usable, follow local guidelines for the disposal of metal and aluminum components.

## Contact Information for Further Support

For further assistance or inquiries regarding safety and product usage, please refer to the manufacturer's guidelines or contact your local dealer.

By following these safety instructions, you can ensure a safe and enjoyable experience with your OPTIC MOUNT & GHOST RING SIGHT SET FOR ROSSI 95 XS SIGHT SYSTEMS. Always prioritize safety and responsible firearm handling.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)