

EXTENDED SLIDE RELEASE FOR GLOCK® 43/43X/48 - TYRANT CNC

EXTENDED SLIDE RELEASE FOR GLOCK 42/43/43X/48 BLACK

[Handgun Parts](#) > [Frame Parts](#) > [Slide Catch Parts](#) > [Slide Catches](#)

Introducing the first-ever Glock Extended Slide Release to be CNC Machined! Made from 6061 Aluminum and hard coat anodized their drop-in replacement Glock slide stop is the perfect upgrade for your pistol. Their Glock extended slide release adds surface area and a raised texture that greatly improves usability for all! It is the perfect upgrade for concealed carry AND competition. Never again will your thumb slip while manipulating your Glock slide release! What is it? This drop-in replacement Glock extended slide stop release lever has a surface area extended over the OEM size. It arrives fully assembled with spring and is offered for multiple Glock models. Why use it? One of the main flaws of the Glock Factory release lever is that it offers very little surface area and/or texture. This results in the operator occasionally slipping when attempting to manipulate the lever. Their Glock slide release offers an extended AND raised surface area to ensure easy manipulation of the Glock slide. It is easy to install, functions great, and looks fantastic! For Generation: All For Gun Model: 42 43 43x 48 Caliber: 9mm Disclaimer: When using a relatively new and fully loaded magazine ensure you are using adequate force when loading the magazine in order to maintain the proper function of this ESR. We always recommend taking the slide out of battery with your hand.



Attributes

- Name: [TYRANT CNC EXTENDED SLIDE RELEASE FOR GLOCK 42/43/43X/48 BLACK](#)
- Manufacturer: [TYRANT CNC](#)
- Product no.: 430109435
- Mfr. No.: TD-GSTOP-48-BLACK
- Caliber: 9 mm Luger
- Finish: Black
- Model: 43,43X,48,42
- Weapon type: Glock
- Delivery weight: 0.181kg
- Shipping height: 25mm
- Shipping width: 121mm
- Shipping length: 102mm

Item details

US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for EXTENDED SLIDE RELEASE FOR GLOCK® 43/43X/48 TYRANT CNC
- About Us

Safety Instruction Guide for EXTENDED SLIDE RELEASE FOR GLOCK® 43/43X/48 TYRANT CNC

Introduction

Thank you for choosing the EXTENDED SLIDE RELEASE FOR GLOCK® 43/43X/48 by TYRANT CNC. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your product. Please read this document thoroughly before installation and use.

General Safety Guidelines

- **Product Safety:** Ensure that you are using this product in accordance with the safety guidelines provided. This product is designed for safe use when installed and operated correctly.
- **Enhanced Recalls:** Stay informed about product recalls and safety notices. In the event of a recall, follow the instructions provided for returning or replacing the product.
- **Online Shopping:** If purchased online, ensure that the seller complies with safety requirements as mandated by the EU General Product Safety Regulation (GPSR).
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors to prevent accidents.
- **EU Contact Point:** For safety inquiries, refer to the designated EU contact point provided by the manufacturer.
- **Rapid Alerts:** Monitor updates regarding product safety through the EU's Safety Gate system.

Specific Safety Precautions for Use

- **Installation Precautions:**
 - Always ensure the firearm is unloaded before beginning installation.
 - Use appropriate tools to avoid damaging the product or firearm.
- **Operational Precautions:**
 - Always handle your firearm with care and in a safe environment.
 - Avoid using excessive force when manipulating the slide release.
 - Ensure that your thumb is positioned securely on the extended surface to prevent slipping.
- **General Use:**
 - Regularly inspect the slide release for wear and tear.
 - If you notice any damage, discontinue use immediately and replace the part.

Instructions for Installation and Usage

Installation Steps

1. **Preparation:**
 - Ensure the firearm is unloaded and pointed in a safe direction.
 - Gather required tools (e.g., screwdriver, punch tool).
2. **Remove the OEM Slide Release:**
 - Locate the OEM slide release on your Glock model.
 - Carefully remove the existing slide release using the appropriate tool.
3. **Install the Extended Slide Release:**
 - Align the new extended slide release with the mounting hole.
 - Insert and secure it in place, ensuring it is fully seated.
4. **Reassemble the Firearm:**
 - Reassemble any parts that were removed during the installation.
 - Ensure everything is functioning correctly before use.

Usage Guidelines

- **Operating the Slide Release:**
 - Use your thumb to engage the slide release.
 - Ensure your grip is firm to prevent slipping.
- **Loading the Magazine:**
 - When using a fully loaded magazine, apply adequate force to ensure proper function.
 - It is recommended to remove the slide from battery using your hand.

Disposal Instructions

- **Proper Disposal:**
 - Dispose of the product in accordance with local regulations.
 - Do not dispose of this product in regular household waste.
 - Consider recycling options where available.

Contact Information for Further Support

For any questions or concerns regarding the EXTENDED SLIDE RELEASE FOR GLOCK® 43/43X/48, please refer to the manufacturer's website or customer service for support.

By following these safety instructions, you can ensure a safer and more effective experience with your product. Always prioritize safety and responsible handling of firearms. Thank you for your attention to these guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk