

# AR-15 SILENT CAPTURED SPRINGS GEN 2 H2 - J P ENTERPRISES

## AR-15 SILENT CAPTURED SPRING GEN 2 H2

[Rifle Parts](#) > [Receiver Parts](#) > [Recoil Parts](#) > [Recoil Springs](#)

The Gen 2 Drop-in captured-spring recoil system helps your AR function more smoothly and quieter without any permanent modifications. The carefully balanced, custom-ground buffer spring, combined with the JP LMOS buffer, greatly reduces friction and vibration - say goodbye to the annoying "spoon over a cheese grater" noise of conventional springs and buffers. Fits buffer tubes for both M4-style collapsible stocks and also, using the included spacer, the longer tubes for fixed rifle stocks. The H2 buffer is heavier than the standard spring. The buffer includes two Tungsten weights in addition to one steel weight. Weighing approximately 4.7 oz. Recommended for use in Short-barreled rifles, suppressed firearms, select fire rifles, and piston-operated rifles. The Auxiliary Spring Rate Kits for the JP Silent Captured Spring allow custom tuning of the device to a given rifle. While the default spring offers the best performance for the widest range of configurations, a simple disassembly and reassembly of the JPSCS with a slightly different spring rate can yield truly optimized performance, particularly for rifles without an adjustable gas block. Benefits of the Gen 2 Silent Captured Spring include: New aluminum guide rod cuts overall weight Heavier masses translate to more buffering mass and chance of bolt bounce Full correspondence between SCS masses and H1, H2 and H3 buffer Interchangeable buffers allow conversion between AR-15 and AR-10 models (and vice versa) Includes spacer to allow for installation in both carbine-length and rifle-length buffer tubes.



### Attributes

- Name: [JP ENTERPRISES AR-15 SILENT CAPTURED SPRING GEN 2 H2](#)
- Manufacturer: [JP ENTERPRISES](#)
- Product no.: 452000211
- Mfr. No.: JPSCS2-15H2
- Weapon type: AR-15
- Delivery weight: 0.313kg
- Shipping height: 64mm
- Shipping width: 66mm
- Shipping length: 226mm
- UPC: 812872023984

### Item details

Made in USA

US export classification: 0A501.x

# Table of Contents

- Startpage
- AR15 Silent Captured Springs Gen 2 H2 Safety Instruction Guide
- About Us

# AR15 Silent Captured Springs Gen 2 H2 Safety Instruction Guide

## Introduction

Thank you for choosing the AR15 Silent Captured Springs Gen 2 H2. This product is designed to enhance the performance of your AR15 rifle by providing a smoother and quieter recoil system. To ensure the safe use of this product, please read and follow the safety instructions outlined in this guide.

## General Safety Guidelines

- Always handle firearms with care and respect.
- Ensure the firearm is unloaded before installation or maintenance.
- Use protective eyewear when working with or around firearms.
- Keep this product out of reach of children and unauthorized users.
- Regularly check for wear and tear on the recoil system and replace as necessary.
- Report any unsafe conditions or accidents to the appropriate authorities.

## Specific Safety Precautions for Use

- Ensure compatibility with your specific AR15 model before installation.
- Do not modify or alter the recoil system in any way.
- Follow the manufacturer's recommendations regarding the use of the H2 buffer and spring.
- Avoid using this product in firearms that are not designed to accommodate it.
- Be aware of the additional weight of the H2 buffer and its impact on overall firearm handling.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather necessary tools for installation (e.g., screwdriver, wrench).
- Ensure the firearm is completely unloaded and safe to work on.

### 2. Installation Steps:

- Remove the existing buffer and spring from the buffer tube.
- Insert the JP LMOS buffer into the buffer tube.
- Carefully install the Gen 2 Silent Captured Spring into the buffer tube.
- If using a fixed rifle stock, use the included spacer to ensure proper fit.
- Reassemble the firearm according to the manufacturer's instructions.

### 3. Usage:

- After installation, conduct a function check to ensure proper operation of the recoil system.
- Test fire the firearm in a safe and controlled environment to confirm performance.
- Monitor the performance of the recoil system during regular use and address any irregularities immediately.

## Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Contact local waste management authorities for guidance on proper disposal methods.

## **Contact Information for Further Support**

For any questions or concerns regarding the AR15 Silent Captured Springs Gen 2 H2, please refer to the manufacturer's customer support resources.

Thank you for your attention to these safety instructions. Your safety and the safe operation of your firearm are of utmost importance.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)