

AR-15 SILENT CAPTURED SPRINGS GEN 2 H2 - J P ENTERPRISES

AR-15 SILENT CAPTURED SPRING GEN 2 H2 W/ ALT SPRING PACK

[Rifle Parts](#) > [Receiver Parts](#) > [Recoil Parts](#) > [Recoil Springs](#)

The Gen 2 Drop-in captured-spring recoil system helps your AR function more smoothly and quieter without any permanent modifications. The carefully balanced, custom-ground buffer spring, combined with the JP LMOS buffer, greatly reduces friction and vibration - say goodbye to the annoying “spoon over a cheese grater” noise of conventional springs and buffers. Fits buffer tubes for both M4-style collapsible stocks and also, using the included spacer, the longer tubes for fixed rifle stocks. The H2 buffer is heavier than the standard spring. The buffer includes two Tungsten weights in addition to one steel weight. Weighing approximately 4.7 oz. Recommended for use in Short-barreled rifles, suppressed firearms, select fire rifles, and piston-operated rifles. The Auxiliary Spring Rate Kits for the JP Silent Captured Spring allow custom tuning of the device to a given rifle. While the default spring offers the best performance for the widest range of configurations, a simple disassembly and reassembly of the JPSCS with a slightly different spring rate can yield truly optimized performance, particularly for rifles without an adjustable gas block. Benefits of the Gen 2 Silent Captured Spring include: New aluminum guide rod cuts overall weight Heavier masses translate to more buffering mass and chance of bolt bounce Full correspondence between SCS masses and H1, H2 and H3 buffer Interchangeable buffers allow conversion between AR-15 and AR-10 models (and vice versa) Includes spacer to allow for installation in both carbine-length and rifle-length buffer tubes.



Attributes

- Name: [J P ENTERPRISES AR-15 SILENT CAPTURED SPRING GEN 2 H2 W/ ALT SPRING PACK](#)
- Manufacturer: [J P ENTERPRISES](#)
- Product no.: 452000212
- Mfr. No.: JPSCS2-15K-H2
- Weapon type: AR-15
- Delivery weight: 0.318kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 343mm
- UPC: 812872024028

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for AR15 Silent Captured Springs Gen 2 H2](#)
- [About Us](#)

Safety Instruction Guide for AR15 Silent Captured Springs Gen 2 H2

Introduction

Thank you for choosing the AR15 Silent Captured Springs Gen 2 H2 by J P Enterprises. This recoil system is designed to enhance the performance of your AR15 rifle, providing smoother and quieter operation. It is essential to follow the safety instructions outlined in this guide to ensure safe and effective use of the product.

General Safety Guidelines

- **Product Safety:** Always ensure the safe use of the recoil system. This product is intended for nonfood applications and complies with EU safety regulations.
- **Enhanced Recalls:** In the event of a product recall, you will be notified through standardized notices. Free remedies will be provided for any dangerous products.
- **Online Shopping:** Purchasing this product online provides the same safety protections as buying in physical stores. Ensure you buy from reputable retailers.
- **Special Consumer Focus:** This product is not intended for use by children. Keep all components out of reach of minors to prevent accidents.
- **EU Contact Point:** For any safety inquiries, please refer to the designated EU contact point provided by the retailer.
- **Rapid Alerts:** Stay informed about any unsafe products through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Read the Manual:** Always read this safety instruction guide thoroughly before use.
- **Check Compatibility:** Ensure that the Silent Captured Springs Gen 2 H2 is compatible with your specific AR15 model.
- **Inspect Before Use:** Regularly inspect the recoil system for any signs of wear or damage. Do not use if any components appear compromised.
- **Proper Handling:** Always handle your firearm responsibly and in accordance with local laws and regulations.
- **Training:** Ensure that all users are trained in the safe handling and operation of firearms.
- **Use Appropriate Ammunition:** Only use ammunition that is suitable for your firearm and the recoil system.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded before beginning installation.
- Remove the existing buffer and spring from the buffer tube.
- Insert the JP Silent Captured Spring into the buffer tube, ensuring it is seated properly.
- If using the spacer, ensure it is installed correctly for compatibility with your buffer tube length.
- Reassemble the buffer tube and ensure all components are secure.

2. Usage:

- After installation, test the functionality of the rifle in a safe environment.
- Monitor the performance of the recoil system during use. If any unusual noises or behaviors occur, cease use immediately and inspect the system.

Disposal Instructions

- Dispose of the product in accordance with local regulations for hazardous materials.
- Do not throw away in regular household waste. Check with your local waste management authority for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the AR15 Silent Captured Springs Gen 2 H2, please refer to the contact information provided by your retailer.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk