

308 AR SILENT CAPTURED SPRINGS GEN 2 H2 - J P ENTERPRISES

308 AR SILENT CAPTURED SPRING GEN 2 H2 W/ ALT SPRING PACK

[Rifle Parts](#) > [Receiver Parts](#) > [Recoil Parts](#) > [Recoil Springs](#)

The Gen 2 Drop-in captured-spring recoil system helps your AR function more smoothly and quieter without any permanent modifications. The carefully balanced, custom-ground buffer spring, combined with the JP LMOS buffer, greatly reduces friction and vibration - say goodbye to the annoying "spoon over a cheese grater" noise of conventional springs and buffers. Fits buffer tubes for both M4-style collapsible stocks and also, using the included spacer, the longer tubes for fixed rifle stocks. The H2 buffer is heavier than the standard spring. The buffer includes two Tungsten weights in addition to one steel weight. Weighing approximately 4.7 oz. Recommended for use in Short-barreled rifles, suppressed firearms, select fire rifles, and piston-operated rifles. The Auxiliary Spring Rate Kits for the JP Silent Captured Spring allow custom tuning of the device to a given rifle. While the default spring offers the best performance for the widest range of configurations, a simple disassembly and reassembly of the JPSCS with a slightly different spring rate can yield truly optimized performance, particularly for rifles without an adjustable gas block. The Heavy Spring System Version have Tungsten Weights and are recommended for Short-Barreled Rifles, Suppressed Weapons, Rifles with an H2/H3 Buffer, Select-Fire Rifles, and Piston-Operated Rifles. Benefits of the Gen 2 Silent Captured Spring include: New aluminum guide rod cuts overall weight Heavier masses translate to more buffering mass and chance of bolt bounce Full correspondence between SCS masses and H1, H2 and H3 buffers Additional mass added to both AR-10 and 9mm models for better, broader function Interchangeable buffers allow conversion between AR-15 and AR-10 models (and vice versa) Includes spacer to allow for installation in both carbine-length and rifle-length buffer tubes.



Attributes

- Name: [JP ENTERPRISES 308 AR SILENT CAPTURED SPRING GEN 2 H2 W/ ALT SPRING PACK](#)
- Manufacturer: [JP ENTERPRISES](#)
- Product no.: 452000216
- Mfr. No.: JPSCS210KH2
- Weapon type: AR .308
- Delivery weight: 0.272kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 343mm
- UPC: 812872024042

Item details

Made in USA
US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for 308 AR Silent Captured Springs Gen 2 H2
- About Us

Safety Instruction Guide for 308 AR Silent Captured Springs Gen 2 H2

Introduction

Thank you for choosing the 308 AR Silent Captured Springs Gen 2 H2 by J P Enterprises. This product is designed to enhance the performance of your AR platform while ensuring a smoother and quieter operation. It is essential to follow the safety guidelines outlined in this document to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure that the product is used only in accordance with the manufacturer's instructions.
- Always handle firearms and related components with care and responsibility.
- Keep the product out of reach of children and unauthorized users.
- Regularly inspect the product for any signs of wear or damage.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay informed about recall updates through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Potential Hazards:** Improper installation or use may lead to malfunction, which can result in injury or damage.
- **Age Restrictions:** This product is intended for use by individuals aged 18 and older. Ensure that younger users are supervised by a responsible adult.
- **Environmental Conditions:** Avoid using the product in extreme weather conditions that may affect its performance.
- **Compatibility:** Ensure that the product is compatible with your specific AR model before installation.
- **Protective Gear:** Always wear appropriate protective gear, such as eye protection, when handling firearms.

Instructions for Installation and Usage

1. Installation:

- Ensure your firearm is unloaded and pointed in a safe direction.
- Remove the existing buffer and spring from your buffer tube.
- Insert the JP Silent Captured Spring into the buffer tube, ensuring it is properly seated.
- If using the spacer, install it according to the manufacturer's instructions for carbine length or rifle length buffer tubes.
- Reassemble your firearm according to the manufacturer's specifications.

2. Usage:

- After installation, conduct a function check to ensure proper operation.
- Regularly clean and maintain the product to ensure optimal performance.
- Monitor the performance of your firearm and the captured spring system during use. If you notice any irregularities, stop using the product and consult a qualified gunsmith.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Contact local waste management authorities for guidance on proper disposal methods.

Contact Information for Further Support

For any safety inquiries or support regarding the 308 AR Silent Captured Springs Gen 2 H2, please refer to the manufacturer's contact details provided on the product packaging or the official website.

By following these safety guidelines, you can ensure a safe and enjoyable experience with your new product. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk