

BLANK DOVETAIL FRONT SIGHT .075" - .075" NOVAK FRONT SIGHT

[Handgun Parts](#) > [Sights](#) > [Front Sights](#)

Strong, Easily Changed Sights For Autos

Dovetail mounted, roll-pinned sights resist shoot-off. Easily changed for different loads or conditions. Full instructions. Unfinished, in-the-white.



Attributes

- Name: [.075" NOVAK FRONT SIGHT](#)
- Manufacturer: [NOVAK](#)
- Product no.: 662645075
- Mfr. No.: DFS02-BLANK
- Colour: Black
- Height: .300
- Model: Commander, Government
- Outline: None
- Style: Blank
- Weapon type: 1911
- Width: .125
- Delivery weight: 0.009kg
- Shipping height: 10mm
- Shipping width: 64mm
- Shipping length: 94mm

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for BLANK DOVETAIL FRONT SIGHT .075"
- About Us

Safety Instruction Guide for BLANK DOVETAIL FRONT SIGHT .075"

Introduction

Thank you for choosing the BLANK DOVETAIL FRONT SIGHT .075". This product is designed for use with 1911 models, including Government and Commander types. It is important to follow these safety instructions carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure that you are familiar with the operation of your firearm before installing or using this front sight.
- Always treat your firearm as if it is loaded, even when you believe it is not.
- Keep this product out of reach of children and unauthorized users.
- Regularly inspect the front sight for any signs of wear or damage.
- If you notice any irregularities, discontinue use immediately and consult a qualified gunsmith.

Specific Safety Precautions for Use

- Use only compatible firearms (1911 models: Government, Commander).
- Ensure that the front sight is securely attached before firing.
- Do not modify the front sight or firearm in any way that could compromise safety.
- When changing the front sight for different loads or conditions, follow the installation instructions carefully to avoid improper fitting.
- Be aware of your surroundings and ensure a safe shooting environment.

Instructions for Installation and Usage

1. Tools Required:

- Appropriate tools for installation (specific tools may vary).
- Safety glasses.

2. Installation Steps:

- Ensure the firearm is unloaded and the chamber is clear.
- Remove the existing front sight if applicable.
- Align the new front sight with the dovetail slot on the firearm.
- Securely fasten the front sight using the roll pin provided.
- Verify that the front sight is properly aligned and secure.

3. Usage:

- After installation, test the sighting in a safe environment.
- Make any necessary adjustments based on personal preference and shooting conditions.

Disposal Instructions

- Dispose of any packaging materials responsibly and in accordance with local regulations.
- If the front sight becomes damaged beyond repair, consult local waste disposal guidelines for proper disposal methods.

Contact Information for Further Support

For any inquiries regarding safety or productrelated questions, please refer to the EUbased contact point provided with your product packaging or documentation.

By adhering to these guidelines, you help ensure not only your safety but also the safety of those around you. Always prioritize safety when handling firearms and their components. Thank you for your attention to these important safety instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk