

# Delta Series AR Front Sight Tool

[Gunsmith Tools](#) > [Sight & Scope Installation Tools](#) > [Sight Adjusting Tools](#)

The Wheeler Delta Series AR Front Sight Tool is a black zinc plated steel, 4-prong front sight tool designed to install and adjust the A2 front sight found on the AR-15, M16 and M4. It is machined from steel and has a black zinc finish to last for years. The key ring serves as a handle and helps keep the small tool accounted for. Can be used with any  $\frac{1}{4}$ " hex driver.

NO IMAGE  
AVAILABLE

## Attributes

- Name: [Delta Series AR Front Sight Tool](#)
- Manufacturer: [Wheeler](#)
- Product no.: EU1001229
- Mfr. No.: 156437
- Weapon type: AR-15
- Delivery weight: 0.05kg
- Shipping height: 37mm
- Shipping width: 99mm
- Shipping length: 119mm
- UPC: 661120564379

# Table of Contents

- Startpage
- Safety Instruction Guide for Wheeler Delta Series AR Front Sight Tool
- About Us

# Safety Instruction Guide for Wheeler Delta Series AR Front Sight Tool

## Introduction

Thank you for choosing the Wheeler Delta Series AR Front Sight Tool. This tool is designed to assist you in installing and adjusting the A2 front sight on your AR15, M16, and M4 firearms. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

## General Safety Guidelines

- Ensure that you are familiar with the operation of your firearm before using this tool.
- Always handle firearms with care and in accordance with the manufacturer's safety guidelines.
- Keep this tool out of the reach of children and unauthorized users.
- Regularly inspect the tool for any signs of damage or wear before use.
- Do not use the tool for any purpose other than intended.
- Report any unsafe products or accidents to the relevant authorities.
- Stay informed about product recalls and safety updates through the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- Always wear appropriate personal protective equipment (PPE), such as safety glasses, when using the tool.
- Ensure the firearm is unloaded and pointed in a safe direction before using the tool.
- Do not exceed the recommended torque when using the tool with a hex driver.
- Store the tool in a secure location when not in use to prevent accidents.
- Be cautious of sharp edges and points on the tool during handling.

## Instructions for Installation and Usage

### 1. Preparation:

- Ensure the firearm is unloaded and safe.
- Gather all necessary tools, including a  $\frac{1}{4}$ " hex driver.

### 2. Installation of the Front Sight:

- Align the front sight tool prongs with the adjustment notches on the A2 front sight.
- Insert the tool into the notches, ensuring a secure fit.

### 3. Adjustment:

- Turn the tool clockwise to raise the front sight and counterclockwise to lower it.
- Make adjustments gradually and check the sight alignment frequently.

### 4. Final Check:

- Once the desired adjustment is made, remove the tool and visually inspect the front sight for proper alignment.
- Store the tool safely after use.

## Disposal Instructions

- Dispose of the tool in accordance with local regulations.
- If the tool is damaged beyond repair, consider recycling the metal components where possible.
- Do not dispose of the tool in general waste.

## Contact Information for Further Support

For any questions or concerns regarding the use of the Wheeler Delta Series AR Front Sight Tool, please reach out to your local retailer or manufacturer's customer service. Ensure you have the product details handy for efficient assistance.

By following these safety instructions, you can ensure a safe and effective experience with the Wheeler Delta Series AR Front Sight Tool. Thank you for prioritizing safety in your firearm maintenance.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)