

ESS Fore-end - MDT Chassis - ESS Forend - NV Rail - 15" (381mm) - BLK

[Rifle Parts](#) > [Build Kits](#) > [Handguards & Rails](#)

ESS comes with a 15" fore-end, but different fore-ends are available if you want a shorter or longer forend and/or attachment rails

NO IMAGE
AVAILABLE

Attributes

- Name: [MDT Chassis - ESS Forend - NV Rail - 15" \(381mm\) - BLK](#)
- Manufacturer: [MDT](#)
- Product no.: EU2004223
- Mfr. No.: 102744-BLK
- Colour: Black
- Material: Aluminum
- Delivery weight: 0.55kg
- Shipping height: 89mm
- Shipping width: 92mm
- Shipping length: 508mm
- UPC: 709951101551

Table of Contents

- [Startpage](#)
- [MDT ESS Foreend Safety Instructions](#)
- [About Us](#)

MDT ESS Foreend Safety Instructions

Introduction

Thank you for choosing the MDT ESS Foreend. This safety instruction guide is designed to help you understand the safe use, installation, and disposal of your product. Please read the following guidelines carefully to ensure your safety and the proper functioning of the chassis.

General Safety Guidelines

- Always handle the product with care to avoid injury.
- Inspect the product before each use to ensure it is in good condition.
- Keep the product out of reach of children and vulnerable individuals.
- Follow all local laws and regulations regarding the use of this product.
- Report any unsafe conditions or incidents to the appropriate authorities.
- Stay informed about product recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the foreend is securely attached to the chassis before use.
- Do not exceed the recommended weight limit for attachments on the rail.
- Avoid using the product in extreme weather conditions that may compromise safety.
- Use only compatible accessories and components designed for the MDT ESS Foreend.
- Wear appropriate protective gear when using the product, especially during installation.

Instructions for Installation and Usage

Installation

1. Prepare Your Workspace:

- Ensure you have a clean, flat surface to work on.
- Gather all necessary tools and components.

2. Attach the Foreend:

- Align the foreend with the chassis mounting points.
- Securely fasten the foreend using the provided screws and tools.
- Doublecheck that the foreend is firmly attached before proceeding.

3. Install the NV Rail:

- Position the NV rail on the foreend as per the manufacturer's specifications.
- Use the provided screws to secure the rail firmly in place.

Usage

• Handling:

- Always carry the chassis in a safe manner to prevent accidents.
- Do not point the chassis at yourself or others during handling.

• Maintenance:

- Regularly clean the chassis and foreend to prevent debris buildup.
- Inspect the attachment points for signs of wear or damage.

- **Storage:**

- Store the product in a dry, safe place away from children and pets.
- Avoid exposing the product to extreme temperatures or humidity.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste.
- Do not dispose of the product in regular household waste.
- Consider recycling components where possible to minimize environmental impact.

Contact Information for Further Support

For any inquiries or support regarding the MDT ESS Foreend, please refer to the manufacturer's customer service resources. Ensure you have your product details ready for a more efficient support experience.

By following these safety instructions, you can ensure the safe and effective use of your MDT ESS Foreend. Thank you for your attention to these guidelines, and enjoy your product responsibly!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk