

ESS Fore-end No Rail 12in ODG

[Rifle Parts](#) > [Build Kits](#) > [Handguards & Rails](#)

ESS comes with a 15" fore-end, but different fore-ends are available if you want a shorter or longer forend and/or attachment rails

NO IMAGE
AVAILABLE

Attributes

- Name: [MDT ESS Fore-end No Rail 12in ODG](#)
- Manufacturer: [MDT](#)
- Product no.: EU2007689
- Mfr. No.: 102743-ODG
- Colour: Olive Drab Green
- Material: Aluminum
- Delivery weight: 0.5kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 300mm
- UPC: 682131929797

Table of Contents

- Startpage
- Safety Instructions for MDT ESS Foreend No Rail 12in ODG
- About Us

Safety Instructions for MDT ESS Foreend No Rail 12in ODG

Introduction

Thank you for choosing the MDT ESS Foreend No Rail 12in ODG. This product is designed to enhance the functionality of your firearm while ensuring safety during use. It is essential to read and understand these safety instructions to ensure a safe and effective experience.

General Safety Guidelines

- Always ensure that the firearm is unloaded before installing or handling the foreend.
- Use the product only for its intended purpose as specified in this manual.
- Keep the foreend and firearm out of reach of children and unauthorized users.
- Regularly inspect the foreend for signs of wear or damage.
- If you notice any defects or issues, discontinue use immediately and seek assistance.

Specific Safety Precautions for Use

- Ensure that the foreend is securely attached to the firearm before use.
- Do not exceed the manufacturer's recommended specifications for attachments or accessories.
- Be aware of your surroundings and ensure a safe shooting environment.
- Always wear appropriate safety gear, including eye and ear protection, when using firearms.
- Follow all local laws and regulations regarding firearm use and modifications.

Instructions for Installation and Usage

Installation

1. Preparation

- Ensure that the firearm is unloaded.
- Gather all necessary tools for installation.

2. Removing the Existing Foreend

- Carefully remove the existing foreend by following the manufacturer's instructions.
- Set aside any components that will be reused.

3. Installing the MDT ESS Foreend

- Align the MDT ESS Foreend with the firearm's mounting system.
- Securely fasten the foreend using the appropriate screws or attachments.
- Doublecheck to ensure that it is tightly secured.

4. Final Inspection

- Inspect the installation to ensure there are no loose parts.
- Confirm that the foreend is properly aligned and securely attached.

Usage

- Always ensure the firearm is pointed in a safe direction.
- When using the foreend, maintain a firm grip and control of the firearm.

- Periodically check the attachment of the foreend during use, especially after extended firing sessions.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the foreend in regular household waste.
- Consider recycling options if available in your area.

Contact Information for Further Support

For any questions or concerns regarding the MDT ESS Foreend No Rail 12in ODG, please refer to your local authorized dealer or the manufacturer's website for assistance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk