

Max Grip Sling (Black)

[Shooting Accessories](#) > [Slings & Sling Swivels](#) > [Slings](#)

The Caldwell Max Grip Slim Sling is adjustable from 20"-41" for full comfort out on the range or the trails. The non-slip ergonomic design is sure to keep your firearm secure while you're out in the wilderness. With quick detach metal sling swivels, the Max Grip Slim Sling is the easiest and quickest way to keep your firearm secure.

NO IMAGE
AVAILABLE

Attributes

- Name: [CALDWELL Max Grip Sling \(Black\)](#)
- Manufacturer: [Caldwell](#)
- Product no.: EU2009897
- Mfr. No.: 1131995
- Colour: Black
- Style: 2-point Sling
- Delivery weight: 0.27kg
- Shipping height: 24mm
- Shipping width: 9mm
- Shipping length: 366mm
- UPC: 661120103592

Table of Contents

- [Startpage](#)
- [Caldwell Max Grip Sling Safety Instructions](#)
- [About Us](#)

Caldwell Max Grip Sling Safety Instructions

Introduction

Thank you for choosing the Caldwell Max Grip Sling. This safety instruction guide is designed to ensure the safe use of your sling, providing essential information on its installation, usage, and disposal. Please read this guide carefully to understand how to use the product safely and effectively.

General Safety Guidelines

- Ensure that the sling is used only for its intended purpose: securing your firearm while in use or during transport.
- Regularly inspect the sling for any signs of wear or damage before each use.
- Keep the sling out of reach of children and vulnerable individuals when not in use.
- Always follow local laws and regulations regarding firearm safety and transportation.
- Report any unsafe products or accidents to the relevant authorities.
- Stay informed about recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Use the sling only with firearms that are compatible with a 2point sling design.
- Ensure that the sling is securely attached to your firearm before use.
- Adjust the sling to fit comfortably and securely, ensuring it does not interfere with your ability to handle the firearm safely.
- Avoid using the sling in wet or slippery conditions to prevent accidental slips.
- Do not overload the sling or use it to carry additional items that may compromise its integrity.
- Always keep the firearm pointed in a safe direction when using the sling.

Instructions for Installation and Usage

1. Installation:

- Identify the attachment points on your firearm where the sling will be secured.
- Attach the quick detach metal sling swivels to the designated points on your firearm.
- Ensure that the swivels are locked in place and that there is no play in the attachment.

2. Adjustment:

- Adjust the length of the sling by sliding the adjuster to achieve a comfortable fit between 20" and 41".
- Test the adjustment by lifting the firearm and ensuring it is secure and comfortable against your body.

3. Usage:

- When using the sling, ensure that it is properly positioned over your shoulder and across your body.
- Always check that the sling does not obstruct your movement or visibility.
- Practice using the sling with an unloaded firearm to become familiar with its operation.

Disposal Instructions

- Dispose of the sling responsibly in accordance with local waste management regulations.
- If the sling is damaged or no longer safe for use, do not attempt to repair it. Instead, dispose of it to

prevent accidental use.

Contact Information for Further Support

For any questions or concerns regarding the Caldwell Max Grip Sling, please reach out to your local Caldwell representative or visit the official Caldwell website for support. Always ensure you have the latest safety information and product updates.

By following these safety instructions, you can ensure a secure and enjoyable experience with your Caldwell Max Grip Sling. Thank you for your commitment to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk