

Free Float Lock Ring for dillon toolhead - Black

[Reloading](#) > [Reloading Presses](#) > [Reloading Press Accessories](#)

Free-Float Lock Ring for Dillon Toolhead allow the sizer and seater dies to float.

This floating action allows the dies to center themselves exactly over each cartridge for the best possible alignment and more concentric ammunition. This free-float lock ring will only fit with free-float toolheads for Dillon XL650 / XL750 or RL550.

Free-Float Lock Rings are sold individually.

One lock ring is included in the price.

NO IMAGE
AVAILABLE

Installation:

The installation of floating lock rings is fairly simple.

1. Completely remove lock rings from the dies and set the dies so that they touch the floorplate (or according to die instructions).
2. Then screw on the lock rings down to the toolhead using hands only.
3. Then carefully un-screw the ring until the small vertical hole first time aligns with the small threaded bore in the toolhead.
4. Screw the small bolt (included) through the ring into the toolhead.
5. Tighten the lock ring with cross bolt.

This is it.

The die should be a little loose inside the toolhead, this is normal.

Attributes

- Name: [ARMANOV Free Float Lock Ring for dillon toolhead - Black](#)
- Manufacturer: [ARMANOV](#)
- Product no.: EU2009934
- Mfr. No.: FFRING-BL
- Colour: Black
- Delivery weight: 0.014kg
- Shipping height: 8mm
- Shipping width: 95mm
- Shipping length: 60mm
- EAN: 0712195456691

Table of Contents

- Startpage
- ARMANOV Free Float Lock Ring for Dillon Toolhead Safety Instruction Guide
- About Us

ARMANOV Free Float Lock Ring for Dillon Toolhead Safety Instruction Guide

Introduction

Thank you for choosing the ARMANOV Free Float Lock Ring for Dillon Toolhead. This product is designed to enhance your reloading experience by allowing the sizer and seater dies to float, ensuring better alignment and more concentric ammunition. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the Free Float Lock Ring by following all instructions. This product is compliant with EU safety regulations.
- **Enhanced Recalls:** Stay informed about any recall notices. In the event of a safety issue, you will be notified through standardized recall notices.
- **Online Shopping:** If purchased online, ensure that the seller complies with safety requirements similar to those of physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Keep out of reach of minors.
- **EU Contact Point:** For safety inquiries, refer to the contact information provided by your retailer or manufacturer.
- **Rapid Alerts:** Monitor the EU's Safety Gate platform for updates regarding any unsafe products.

Specific Safety Precautions for Use

• Hazard Identification:

- Improper installation may lead to misalignment of dies, resulting in unsafe ammunition.
- Ensure that the lock ring is securely fastened to prevent accidental loosening during operation.

• Avoiding Hazards:

- Always inspect the lock ring and toolhead for any signs of damage before use.
- Do not force the lock ring onto the toolhead; it should fit comfortably without excessive pressure.

• Age Restrictions:

This product is intended for use by individuals who are 18 years or older. Ensure that younger individuals do not handle this product without supervision.

Instructions for Installation and Usage

1. Preparation:

- Completely remove any existing lock rings from the dies.
- Set the dies so that they touch the floorplate or follow specific die instructions.

2. Installation:

- Handtighten the lock rings onto the toolhead. Do not use tools at this stage.
- Carefully unscrew the ring until the small vertical hole aligns with the small threaded bore in the toolhead.
- Insert the small bolt (included) through the ring into the toolhead.
- Tighten the lock ring with the cross bolt to secure it in place.
- Note: The die should be a little loose inside the toolhead; this is normal.

3. Usage:

- After installation, ensure that the dies are centered over the cartridges during reloading.
- Regularly check the tightness of the lock ring and the alignment of the dies.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste. Contact your local waste management authority for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the ARMANOV Free Float Lock Ring for Dillon Toolhead, please refer to the contact information provided by your retailer or manufacturer. It is important to have access to support for any safety inquiries or product issues.

Thank you for your attention to these safety instructions. By following these guidelines, you can ensure a safe and effective reloading experience with the ARMANOV Free Float Lock Ring for Dillon Toolhead.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk