

Clamp Lock Short Bars

[Shooting Accessories](#) > [Duty Gear](#)

The Clamp Lock Short Bars are used to mount the Clamp Lock to a belt or strap up to 3,8cm in width. NOTE You will need at least one Clamp Lock OR Slide Lock AND one RP M, QD P, or Anywhere Mount

NO IMAGE
AVAILABLE

Attributes

- Name: [Clamp Lock Short Bars](#)
- Manufacturer: [OBI SYSTEMS](#)
- Product no.: EU2013648
- Mfr. No.: OBi01006-BLK
- Colour: Black
- Delivery weight: 1kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 100mm
- UPC: 767637840880

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for Clamp Lock Short Bars](#)
- [About Us](#)

Safety Instruction Guide for Clamp Lock Short Bars

Introduction

Thank you for choosing the Clamp Lock Short Bars. These bars are designed to securely mount the Clamp Lock to belts or straps up to 3.8 cm in width. This guide provides important safety instructions and guidelines to ensure safe usage and compliance with EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure that the Clamp Lock Short Bars are used only for their intended purpose.
- Regularly inspect the product for any signs of wear or damage before each use.
- Do not exceed the maximum width of 3.8 cm for belts or straps.
- Keep the product out of reach of children to avoid any potential hazards.
- In case of any defect or malfunction, discontinue use immediately and report it to the appropriate authorities.
- Stay informed about product recalls by checking the EU Safety Gate platform.

Specific Safety Precautions for Use

- Always ensure a secure attachment of the Clamp Lock to the belt or strap.
- Avoid using the product in environments where it may be exposed to extreme temperatures or harsh chemicals.
- Do not modify the Clamp Lock Short Bars or use them in a manner not specified in the instructions.
- If using the product in conjunction with other accessories (e.g., Slide Lock, RP M, QD P, or Anywhere Mount), ensure compatibility before use.
- Be cautious of sharp edges or points during installation and usage.

Instructions for Installation and Usage

1. Installation:

- Identify the belt or strap where the Clamp Lock will be mounted.
- Ensure that the width of the belt or strap does not exceed 3.8 cm.
- Slide the Clamp Lock Short Bars onto the belt or strap, ensuring they fit securely.
- If using additional mounts (Slide Lock, RP M, QD P, or Anywhere Mount), follow the specific installation instructions for those products.

2. Usage:

- Once installed, verify that the Clamp Lock is securely fastened.
- Avoid overloading the Clamp Lock with excessive weight beyond its designed capacity.
- Regularly check the stability of the installation during use to prevent accidents.

Disposal Instructions

- Dispose of the Clamp Lock Short Bars in accordance with local regulations.
- Do not dispose of the product in regular household waste. Instead, utilize designated recycling facilities for plastic and metal components.
- Ensure that any damaged parts are disposed of safely to prevent injury to others.

Contact Information for Further Support

For any inquiries regarding the safety or usage of the Clamp Lock Short Bars, please reach out to the manufacturer or an authorized distributor. Ensure to keep all packaging and documentation for reference.

By following these safety instructions, you can ensure proper use and maintenance of the Clamp Lock Short Bars, promoting safety and longevity of the product. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk