

# Henry Lok Lever Pistol Grip Stock Set - Henry M-LOK Lever Pistol Grip Stock Set (FDE)

[Rifle Parts](#) > [Stock Parts](#) > [Rifle Stocks](#)

Fits: Henry rifles (excluding models with a straight grip stock, Golden Boys, Color Case Hardened 45-70 (H010GCC), Brass Receiver models, Long Rangers, Single Shots, .22 Rimfire, and Barrel Band models).

## Product Features:

Material: Machined from a single piece of billet aluminum for increased rigidity and reduced weight. Handguard: 13.25" (33.65 cm) long, 1.5" (3.8 cm) wide, 1.6" (4.1 cm) high, weight: 5.8 oz (164 g). Functions: 24 M-LOK slots and 4 flush cup holes for sling swivels. Loading port cutout for top-off capability. Enhanced compatibility with shortened barrels and suppressors. 4 set screws for rock-solid bedding and lateral shift elimination. Increased grip with ergonomic design for better comfort. Stock (Buttstock): Tough, weatherproof 6061 billet aluminum, weight: 22 oz (623 g). Adjustable comb height and length-of-pull for a perfect fit. AR-style 6-position butt plate with "Made in Texas" Dead Blow recoil pad. M-LOK accessory panel with two sling swivel holes. Package Includes:

Ranger Point M-LOK Handguard Ranger Point Adjustable Buttstock with cheek riser and M-LOK accessory panel.

NO IMAGE  
AVAILABLE

## Attributes

- Name: [Henry M-LOK Lever Pistol Grip Stock Set \(FDE\)](#)
- Manufacturer: [RANGER POINT](#)
- Product no.: EU2014728
- Mfr. No.: 7000
- Weapon type: Henry
- Delivery weight: 10.89kg
- Shipping height: 101.6mm
- Shipping width: 152.4mm
- Shipping length: 431.8mm
- UPC: 850068664658

# Table of Contents

- Startpage
- Henry MLOK Lever Pistol Grip Stock Set Safety Instructions
- About Us

# Henry MLOK Lever Pistol Grip Stock Set Safety Instructions

## Introduction

Thank you for choosing the Henry MLOK Lever Pistol Grip Stock Set. This guide provides essential safety instructions to ensure the safe use and installation of your product. Please read this document carefully to understand the safety guidelines and best practices associated with your new stock set.

## General Safety Guidelines

- Ensure that the stock set is compatible with your Henry rifle model. It is not suitable for models with a straight grip stock, Golden Boys, Color Case Hardened 4570 (H010GCC), Brass Receiver models, Long Rangers, Single Shots, .22 Rimfire, and Barrel Band models.
- Always handle firearms safely and responsibly. Follow all local laws and regulations regarding firearm ownership and usage.
- Regularly inspect the stock set for any signs of damage or wear. Do not use the stock if it shows signs of structural failure.
- Keep the stock set and all firearms out of reach of children and unauthorized users.

## Specific Safety Precautions for Use

- Before installation, ensure that the firearm is unloaded and the action is open.
- Wear safety glasses when performing any installation or maintenance tasks to protect your eyes from debris.
- Use tools that are appropriate for the installation process. Avoid using excessive force that may damage the stock or firearm.
- Be aware of the weight of the stock set. The handguard weighs 5.8 oz (164 g) and the buttstock weighs 22 oz (623 g). Ensure your firearm can accommodate this weight without compromising balance and handling.
- The adjustable comb height and lengthofpull should be set according to the user's comfort and shooting style. Improper adjustments may lead to reduced accuracy or injury.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools, including a screwdriver and any other tools recommended by the manufacturer.
- Ensure your workspace is clean and free of distractions.

### 2. Installation of the Handguard:

- Remove any existing handguard from your rifle, following the manufacturer's instructions.
- Align the new handguard with the mounting points on your rifle.
- Secure the handguard using the provided set screws. Ensure they are tightened firmly but do not overtighten to avoid damaging the stock.

### 3. Installation of the Buttstock:

- Remove the existing buttstock from your rifle.
- Attach the new buttstock by aligning it with the buffer tube and securing it according to the manufacturer's instructions.

- Adjust the comb height and length of pull to fit your shooting style.

#### **4. Final Checks:**

- Once both components are installed, conduct a thorough inspection to ensure everything is secure and properly aligned.
- Test the functionality of the stock set by cycling the action of your rifle without ammunition to ensure there are no obstructions.

#### **5. Usage:**

- When using your rifle equipped with the new stock set, maintain a proper shooting stance and grip.
- Regularly check the tightness of the handguard and buttstock during use to ensure they remain secure.

## **Disposal Instructions**

- Dispose of any packaging materials responsibly by following your local recycling guidelines.
- If the stock set becomes damaged beyond repair, contact your local waste management service for instructions on safe disposal methods.

## **Contact Information for Further Support**

For any inquiries regarding safety, installation, or maintenance of the Henry MLOK Lever Pistol Grip Stock Set, please contact the manufacturer or your local retailer for assistance.

By adhering to these safety instructions, you can ensure a safe and enjoyable experience with your Henry MLOK Lever Pistol Grip Stock Set. Always prioritize safety and responsibility when handling firearms and related accessories.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)