

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP P4FL 1cm cw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP P4FL 1cm cw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015752
- Mfr. No.: 667-911-972-G9-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537010831

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides essential safety information to ensure the safe and effective use of your riflescope. Please read this manual carefully before installation and use.

General Safety Guidelines

To ensure your safety and the safety of others, please follow these guidelines:

- Ensure that the riflescope is used only for its intended purpose.
- Keep the riflescope out of reach of children and vulnerable individuals.
- Regularly inspect the riflescope for any signs of damage or malfunction before use.
- Always follow local laws and regulations regarding the use of firearms and optics.
- Never point the riflescope at anything you do not intend to shoot.
- Use appropriate protective eyewear when using firearms equipped with this riflescope.

Specific Safety Precautions for Use

When using the 3-20x50 PM II Ultra Short Riflescope, please adhere to the following precautions:

- Do not use the riflescope if it is damaged or has been dropped.
- Avoid exposing the riflescope to extreme temperatures or moisture, as this can affect its performance.
- When adjusting the magnification or other settings, do so only when the firearm is pointed in a safe direction.
- Be cautious when using the illuminated reticle feature, as bright settings may impair your vision in lowlight conditions.
- Ensure that the riflescope is securely mounted before use to prevent it from shifting during operation.

Instructions for Installation and Usage

Follow these steps for the proper installation and usage of your riflescope:

1. Installation:

- Choose a suitable mounting platform on your firearm that is compatible with a 34 mm main tube.
- Securely attach the riflescope to the mount, ensuring it is level and aligned with the barrel.
- Tighten the mounting screws according to the manufacturer's specifications to avoid loosening during use.

2. Adjusting the Scope:

- Set the magnification to your desired level using the magnification ring.
- Adjust the side parallax from approximately 25 m to infinity as needed for your shooting distance.
- Set the elevation and windage turrets to zero before making adjustments for accuracy.

3. Using the Riflescope:

- Position your eye approximately 90 mm from the eyepiece for optimal viewing.
- Use the exit pupil range of approximately 11.4-2.5 mm to ensure a clear sight picture.
- When ready to shoot, ensure that the firearm is stable and pointed safely.

Disposal Instructions

When the riflescope has reached the end of its life cycle or is no longer in use, please dispose of it responsibly:

- Do not dispose of the riflescope in regular household waste.
- Check local regulations for proper disposal methods for optical devices.
- Consider recycling options for the materials used in the riflescope.

Contact Information for Further Support

For any safety inquiries or concerns regarding the 3-20x50 PM II Ultra Short Riflescope, please refer to the contact information provided with your product packaging or visit the manufacturer's website.

Conclusion

By following this safety instruction guide, you can ensure a safe and enjoyable experience with your 3-20x50 PM II Ultra Short Riflescope. Always prioritize safety and responsibility when using firearms and optics. Thank you for your attention to these important safety guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk