

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP TR²ID 1cm cw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP TR²ID 1cm cw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015764
- Mfr. No.: 667-911-432-M3-I6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537070958

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for 3-20x50 PM II Ultra Short Rifle Scope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Rifle Scope from Schmidt and Bender. This guide provides essential safety information to ensure the safe and effective use of your rifle scope. Please read this guide carefully and follow all instructions to avoid potential hazards.

General Safety Guidelines

- Ensure that the rifle scope is used only for its intended purpose.
- Keep the rifle scope out of reach of children and unauthorized users.
- Always handle the rifle scope with care to prevent damage.
- Regularly inspect the rifle scope for any signs of wear or damage before use.
- Use the rifle scope in a safe environment, free from distractions and hazards.
- Follow all local laws and regulations regarding the use of firearms and optics.

Specific Safety Precautions for Use

- Always ensure the rifle is unloaded when attaching or adjusting the rifle scope.
- Use appropriate eye protection when using the rifle scope.
- Avoid looking directly at the sun through the rifle scope, as this can cause severe eye damage.
- Ensure the rifle scope is securely mounted to prevent it from loosening during use.
- Do not modify the rifle scope in any way, as this can compromise its safety and performance.
- Be aware of your surroundings and ensure a clear line of sight before firing.

Instructions for Installation and Usage

Installation

1. Mounting the Rifle Scope:

- Select a suitable mounting platform on your rifle.
- Ensure the mounting rings are compatible with the 34 mm main tube of the rifle scope.
- Securely attach the rifle scope to the mounting platform following the manufacturer's instructions.
- Tighten the mounting screws evenly to avoid misalignment.

2. Adjusting the Reticle:

- Before use, ensure the reticle is correctly aligned for accurate shooting.
- Refer to the specific instructions provided with the rifle scope for reticle adjustments.

3. Setting the Parallax:

- Adjust the side parallax setting based on your shooting distance (from approx. 25 m to infinity).
- Ensure the parallax is set correctly to enhance accuracy.

Usage

1. Magnification Adjustment:

- Use the magnification ring to adjust the zoom level from 3x to 20x as needed.

- Start with a lower magnification for target acquisition and increase as necessary.

2. Field of View:

- Be aware of the field of view, which spans roughly 13.0-2.1 m at 100 m.
- Use lower magnification for broader situational awareness.

3. Exit Pupil and Eye Relief:

- Maintain a distance of approximately 90 mm from the eyepiece for optimal eye relief.
- Ensure the exit pupil is positioned correctly to gather sufficient light for clear visibility.

Disposal Instructions

- Dispose of the riflescope according to local regulations for electronic waste and optical devices.
- Do not throw the riflescope in general waste.
- Contact local waste management authorities for proper disposal methods.

Contact Information for Further Support

For any safety inquiries or assistance with your 3-20x50 PM II Ultra Short Riflescope, please refer to the manufacturer's contact details included with your product packaging.

By adhering to these safety guidelines, you can ensure a safe and enjoyable experience with your riflescope. Always prioritize safety and responsible usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk