

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP TR²ID 1cm ccw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP TR²ID 1cm ccw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015769
- Mfr. No.: 667-911-432-G8-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537070811

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your riflescope. Please read and follow these instructions carefully to maximize your safety and performance while using the product.

General Safety Guidelines

- Ensure that you handle the riflescope responsibly and only for its intended purpose.
- Always treat the riflescope as if it is loaded, even when it is not.
- Keep the riflescope out of reach of children and unauthorized users.
- Be aware of your surroundings and ensure you have a clear line of sight before using the riflescope.
- Regularly inspect the riflescope for any signs of damage or wear. Do not use if damaged.
- Follow all local laws and regulations regarding the use of firearms and optics.

Specific Safety Precautions for Use

- **Magnification Range:** The 3-20x magnification allows for versatile shooting distances. Use appropriate magnification based on your target distance.
- **Objective Lens Diameter:** The 50 mm objective lens provides enhanced light transmission. Avoid using in extremely lowlight conditions without proper illumination.
- **Field of View:** Be mindful of the field of view of approximately 13.0-2.1 m at 100 m. Ensure you have a clear view of your target and surroundings.
- **Exit Pupil and Eye Relief:** The exit pupil ranges from 11.4-2.5 mm, and the eye relief is approximately 90 mm. Maintain a proper distance from the eyepiece to avoid recoil injuries.
- **Parallax Adjustment:** Utilize the side parallax adjustment for precise aiming, especially at distances starting from 25 m to infinity.
- **Illuminated Reticle:** Use the first focal plane illuminated reticle options responsibly, ensuring it does not distract from your target focus.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting platform that can accommodate the 34 mm main tube.
- Securely attach the riflescope to the firearm using appropriate rings and bases.
- Ensure the riflescope is level and aligned with the barrel for optimal accuracy.

2. Usage:

- Before use, familiarize yourself with the controls, including the magnification ring, parallax adjustment, and elevation turret.
- Adjust the magnification according to your shooting needs.
- Set the parallax adjustment to match your target distance for improved accuracy.
- Always check the reticle illumination before use to ensure visibility in varying light conditions.
- Practice safe shooting habits, including proper stance, grip, and trigger control.

Disposal Instructions

- When the riflescope has reached the end of its life or is no longer usable, dispose of it responsibly.
- Follow local regulations regarding the disposal of optical devices and firearms accessories.
- If applicable, consider recycling components of the riflescope to reduce environmental impact.

Contact Information for Further Support

For any safety inquiries or additional support regarding your 3-20x50 PM II Ultra Short riflescope, please refer to the manufacturer's website or authorized dealers for assistance.

By adhering to these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your 3-20x50 PM II Ultra Short riflescope. Always prioritize safety and responsible handling to protect yourself and those around you.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk