

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP MSR2 1cm ccw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP MSR2 1cm ccw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015773
- Mfr. No.: 667-911-822-F1-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537030143

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides essential safety instructions and information to ensure the safe and effective use of your riflescope. Please read this guide carefully before using the product.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the riflescope by following all instructions. This product is designed for highperformance engagements and should be used responsibly.
- **Enhanced Recalls:** Stay informed about any product recalls. If a recall is issued, follow the instructions provided for returning or remedying the product.
- **Online Shopping:** If purchased online, ensure that the retailer complies with safety requirements as mandated by EU regulations.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors.
- **EU Contact Point:** For any safety inquiries, refer to the contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Check the EU's Safety Gate platform regularly for updates on any unsafe products.

Specific Safety Precautions for Use

- **Avoid Eye Injury:** Always use protective eyewear when using the riflescope. The exit pupil can lead to eye strain or injury if not used correctly.
- **Proper Handling:** Handle the riflescope with care. Avoid dropping or knocking it against hard surfaces, as this may damage the optical components.
- **Secure Mounting:** Ensure the riflescope is securely mounted to your firearm. Loose mounting can lead to misalignment and potential accidents.
- **Environmental Conditions:** Do not use the riflescope in extreme weather conditions (e.g., heavy rain, snow, or high humidity) that may affect its performance.
- **Cleaning:** Use a soft, dry cloth to clean the lenses. Avoid using abrasive materials or harsh chemicals that may scratch or damage the optical surfaces.

Instructions for Installation and Usage

1. Installation:

- Ensure your firearm is unloaded before beginning the installation process.
- Use the appropriate mounting rings compatible with the 34 mm main tube diameter.
- Align the riflescope with the barrel of the firearm, ensuring it is level.
- Tighten the mounting screws securely, but do not overtighten to avoid damage.

2. Usage:

- **Adjusting Magnification:** Rotate the magnification ring to set the desired level between 3x and 20x.
- **Focusing the Reticle:** Adjust the side parallax knob to ensure the reticle is clear at your target distance.
- **Eye Relief:** Position your eye approximately 90 mm from the eyepiece to ensure a clear sight picture without any risk of recoil injury.

- **Field of View:** Be aware of the field of view (approx. 13.0–2.1 m @100 m) to maintain situational awareness while shooting.

Disposal Instructions

- Follow local regulations for the disposal of optical devices. Do not dispose of the riflescope in regular household waste.
- If the product is damaged or no longer in use, consider returning it to the retailer for proper disposal or recycling.

Contact Information for Further Support

For any questions or concerns regarding the 3-20x50 PM II Ultra Short Riflescope, please refer to the contact details provided by your retailer or manufacturer. Regularly check for updates on safety and maintenance.

Thank you for following these safety instructions. Enjoy your shooting experience with the 3-20x50 PM II Ultra Short Riflescope.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk