

## 3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP P4FL 1cm cw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×  
Objective Lens Diameter: 50 mm  
Main Tube Diameter: 34 mm  
Field of View: approx. 13.0–2.1 m @100 m  
Exit Pupil: approx. 11.4–2.5 mm  
Eye Relief: approx. 90 mm  
Length: approx. 340 mm  
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

### Attributes

- Name: [3-20x50 PM II Ultra Short LP P4FL 1cm cw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015787
- Mfr. No.: 667-945-972-F2-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537011333

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

# Safety Instruction Guide for 3-20x50 PM II Ultra Short Riflescope

## Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your riflescope. Please read through this document carefully to understand how to operate and maintain your product safely.

## General Safety Guidelines

- Always handle the riflescope with care to prevent damage and ensure safety.
- Ensure that the riflescope is mounted securely on your firearm before use.
- Be aware of your surroundings and ensure that you have a clear line of sight before aiming.
- Keep the riflescope and all related equipment out of reach of children and unauthorized users.
- Regularly check for any signs of wear or damage on the riflescope and its mounting.
- Follow all local laws and regulations regarding the use of firearms and optics.

## Specific Safety Precautions for Use

- **Avoid Direct Eye Exposure:** Never look directly into the sun or any bright light source through the riflescope, as it may cause permanent eye damage.
- **Proper Eye Relief:** Ensure that you maintain the appropriate eye relief (approx. 90 mm) to avoid injury from recoil.
- **Secure Mounting:** Always check that the riflescope is securely mounted to prevent it from loosening during use.
- **Parallax Adjustment:** Make sure to adjust the side parallax to the appropriate distance (from approx. 25 m to infinity) to ensure accuracy and safety.
- **Illuminated Reticle Caution:** Use the illuminated reticle features responsibly and avoid using them in situations where they may distract you or others.

## Instructions for Installation and Usage

### 1. Installation:

- Select a suitable mounting platform for your riflescope.
- Ensure that the mounting rings are compatible with the 34 mm main tube diameter.
- Securely attach the riflescope to the firearm, ensuring it is level and properly aligned.
- Tighten the mounting screws according to the manufacturer's specifications to prevent movement during use.

### 2. Usage:

- Adjust the magnification from 3× to 20× as needed for your shooting distance.
- Use the objective lens diameter of 50 mm to maximize light transmission for better visibility.
- Regularly check the field of view (approx. 13.0–2.1 m at 100 m) to maintain situational awareness.
- Make adjustments to the elevation turret as necessary for precision shooting.
- After use, cover the lenses with protective caps to prevent scratches and dust accumulation.

## Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic and optical equipment.
- Do not dispose of the riflescope in regular household waste.

- Consider recycling options for materials that can be reused.

## **Contact Information for Further Support**

For any safety inquiries or issues related to the 3-20x50 PM II Ultra Short Riflescope, please contact your local retailer or authorized distributor. They will provide assistance and guidance regarding your product.

By following these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your 3-20x50 PM II Ultra Short Riflescope. Thank you for your attention to safety, and enjoy your shooting experience!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)