

# 3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×  
Objective Lens Diameter: 50 mm  
Main Tube Diameter: 34 mm  
Field of View: approx. 13.0–2.1 m @100 m  
Exit Pupil: approx. 11.4–2.5 mm  
Eye Relief: approx. 90 mm  
Length: approx. 340 mm  
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

## Attributes

- Name: [3-20x50 PM II Ultra Short LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015796
- Mfr. No.: 667-945-532-G8-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537011876

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

# Safety Instruction Guide for 3-20x50 PM II Ultra Short Riflescope

## Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope by Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your riflescope. Please read this guide carefully before using the product.

## General Safety Guidelines

- Always handle the riflescope with care to prevent damage.
- Ensure that the riflescope is mounted securely on your firearm before use.
- Do not use the riflescope if it is damaged or malfunctioning.
- Keep the riflescope out of reach of children and vulnerable individuals.
- Always follow local laws and regulations regarding the use of firearms and optical devices.
- Regularly inspect the riflescope for signs of wear or damage.
- Report any unsafe product conditions to the appropriate authorities.

## Specific Safety Precautions for Use

- Use the riflescope only for its intended purpose: as an optical sighting device for firearms.
- Avoid looking directly at the sun through the riflescope, as this can cause serious eye injury.
- Maintain a safe distance from the firearm's muzzle when using the riflescope.
- Ensure that the area is clear of people and obstacles before aiming and firing.
- Use appropriate eye protection when shooting to prevent injury.
- Be aware of your surroundings and ensure a safe shooting environment.

## Instructions for Installation and Usage

### Installation

#### 1. Mounting the Riflescope

- Select a suitable mounting base for your firearm.
- Securely attach the riflescope to the mounting base using the provided rings and screws.
- Ensure that the riflescope is aligned properly with the firearm's barrel.

#### 2. Adjusting the Reticle

- After mounting, adjust the reticle to ensure it is level and centered in the field of view.
- Use the windage and elevation turrets for precise adjustments.

#### 3. Parallax Adjustment

- Adjust the side parallax knob to eliminate parallax error at your shooting distance.

### Usage

#### 1. Adjusting Magnification

- Use the magnification dial to set the desired level of zoom for your shooting conditions.

## 2. **Eye Relief**

- Position your eye at the recommended distance (approximately 90 mm) from the eyepiece to avoid recoil injury.

## 3. **Field of View**

- Be mindful of the field of view (approx. 13.0–2.1 m at 100 m) to maintain situational awareness.

## 4. **Illumination**

- If applicable, activate the illuminated reticle for enhanced visibility in low light conditions.

## **Disposal Instructions**

- Dispose of the riflescope in accordance with local regulations regarding electronic and optical waste.
- Do not dispose of the product in regular household waste.
- Consider recycling options for the materials used in the riflescope.

## **Contact Information for Further Support**

For any inquiries regarding safety or product issues, please contact your local authorized dealer or visit the manufacturer's website for support resources.

By adhering to these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your 3-20x50 PM II Ultra Short Riflescope. Thank you for your attention to safety and responsible use.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)