

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP MSR2 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP MSR2 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015798
- Mfr. No.: 667-945-822-F1-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537030266

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure safe and effective use of your riflescope. It is important to read and understand this information before using the product to minimize risks and enhance your shooting experience.

General Safety Guidelines

- Always handle the riflescope with care to avoid damage.
- Ensure that the riflescope is mounted securely to your firearm before use.
- Do not look directly at the sun or other bright light sources through the riflescope, as this may cause permanent eye damage.
- Always treat firearms as if they are loaded and follow all safety protocols associated with firearm use.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of wear or damage before use.
- If you notice any irregularities or malfunctions, cease use immediately and seek professional assistance.

Specific Safety Precautions for Use

- Use the riflescope only for its intended purpose—aiming at targets and shooting.
- Always ensure that your shooting area is safe and that there are no obstacles or people in the line of fire.
- When adjusting the magnification or other settings, do so with the rifle pointed in a safe direction.
- Be aware of your surroundings and ensure that you have a clear view of your target.
- Use appropriate eye protection while shooting to protect against potential debris or recoil.

Instructions for Installation and Usage

• Installation:

- Ensure you have the necessary tools for mounting the riflescope.
- Select a suitable mounting platform on your firearm that can accommodate the 34 mm main tube.
- Secure the riflescope in place according to the manufacturer's instructions, ensuring it is level and aligned with the firearm's barrel.
- Check that all screws and mounts are tightened properly before use.

• Usage:

- Adjust the magnification by rotating the magnification ring to the desired setting (3-20×).
- Use the side parallax adjustment to set the focus from approximately 25 m to infinity for optimal clarity.
- Ensure that the eye relief is set to approximately 90 mm for comfortable viewing.
- Before taking a shot, verify that the exit pupil is within the range of 11.4-2.5 mm for maximum lightgathering capability.
- Utilize the illuminated reticle options for improved visibility in lowlight conditions.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and hazardous materials.

- Do not dispose of the riflescope in regular household waste.
- Contact local waste management authorities for guidance on proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the safety and use of your 3-20x50 PM II Ultra Short Riflescope, please refer to the manufacturer's website or contact their customer service. It is important to have access to support for any issues that may arise.

By following these guidelines and instructions, you can ensure a safe and enjoyable experience with your riflescope. Always prioritize safety and responsible handling when using firearms and associated equipment.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk