

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP TR²ID 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP TR²ID 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015799
- Mfr. No.: 667-945-432-F1-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537070972

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-20x50 PM II Ultra Short](#)
- [About Us](#)

Safety Instruction Guide for 3-20x50 PM II Ultra Short

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this document carefully to understand how to handle, install, and maintain your riflescope safely.

General Safety Guidelines

- Ensure that the riflescope is used only for its intended purpose—aiming and shooting with a firearm.
- Always follow local laws and regulations regarding the use of firearms and optics.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or wear that could affect its performance or safety.
- Do not attempt to disassemble or modify the riflescope, as this may compromise its safety and warranty.
- Use appropriate eye protection when using the riflescope to prevent injury from recoil or accidental discharge.

Specific Safety Precautions for Use

- Always ensure the firearm is pointed in a safe direction when mounting or adjusting the riflescope.
- Confirm that the firearm is unloaded before installing or adjusting the riflescope.
- Be aware of your surroundings and ensure a clear line of sight before using the riflescope.
- Avoid using the riflescope in extreme weather conditions, such as heavy rain or snow, unless it is specifically rated for such use.
- Do not expose the riflescope to excessive heat or direct sunlight for prolonged periods, as this may damage the optical components.
- Use the riflescope only within its specified magnification range to maintain optimal performance and safety.

Instructions for Installation and Usage

Installation

1. Mounting the Riflescope:

- Select a suitable mounting base compatible with your firearm.
- Securely attach the riflescope to the base according to the manufacturer's instructions, ensuring it is level and aligned.
- Tighten the mounting screws to the manufacturer's recommended torque specifications.

2. Adjusting the Scope:

- Adjust the eye relief by moving the riflescope forward or backward until a full field of view is achieved.
- Set the parallax adjustment according to the distance you will be shooting (from approx. 25 m to infinity).
- Ensure that the reticle is visible and correctly illuminated if using the illuminated reticle option.

Usage

1. Focusing:

- Look through the riflescope and adjust the diopter setting until the reticle appears sharp and clear.

2. Shooting:

- Assume a stable shooting position and ensure that the firearm is securely supported.
- Use the elevation and windage turrets to make necessary adjustments for accurate shooting.
- Always maintain proper trigger discipline and follow all firearm safety protocols.

Disposal Instructions

- Dispose of the riflescope and its components in accordance with local regulations regarding electronic waste and optical devices.
- Do not dispose of the product in regular household waste.
- If the product is damaged or no longer functional, contact a local waste management facility for guidance on proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the 3-20x50 PM II Ultra Short riflescope, please refer to the manufacturer's contact details included in the product packaging or visit the official website for support resources.

By following these safety instructions, you contribute to a safer shooting experience and ensure the longevity and performance of your 3-20x50 PM II Ultra Short riflescope. Thank you for prioritizing safety and compliance with the EU General Product Safety Regulation.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk