

3-20x50 PM II Ultra Short - 5-20x50 PM II Ultra Short LPI TREMOR5 1cm cw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [5-20x50 PM II Ultra Short LPI TREMOR5 1cm cw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015807
- Mfr. No.: 173-911-562-F2-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537063721

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure safe and effective use of the product. Please read the entire guide carefully before using the riflescope.

General Safety Guidelines

- Ensure the riflescope is used only for its intended purpose.
- Always handle the riflescope with care to prevent damage.
- Keep the riflescope out of reach of children and vulnerable individuals.
- Regularly inspect the riflescope for any signs of damage or wear.
- If any parts are damaged, do not use the riflescope until it has been repaired by a qualified technician.
- Be aware of your surroundings and ensure safe shooting practices at all times.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- **Avoid Eye Injury:** Always use proper eye protection when using the riflescope.
- **Check Mounting:** Ensure that the riflescope is securely mounted to your rifle before use.
- **Parallax Adjustment:** Adjust the side parallax according to your shooting distance to ensure accurate targeting.
- **Lighting Conditions:** Be mindful of lighting conditions; the exit pupil provides optimal viewing in low light.
- **Handling:** Avoid touching the lens with your fingers to prevent smudging and reduce optical performance.
- **Stability:** Use the riflescope on stable platforms to maintain accuracy and prevent accidents.
- **Weight Considerations:** Be aware of the riflescope's weight when mounted on lighter firearms to ensure balance and control.

Instructions for Installation and Usage

• Installation:

1. Select a suitable mounting platform on your rifle.
2. Securely attach the riflescope using the provided rings and mounts.
3. Ensure the riflescope is level and aligned with the rifle barrel.
4. Tighten the mounting screws without overtightening to avoid damage.

• Usage:

1. Adjust the magnification according to your shooting needs (3-20x).
2. Set the parallax adjustment based on your target distance (from approx. 25 m to infinity).
3. Position your eye approximately 90 mm from the eyepiece for optimal viewing.
4. Utilize the illuminated reticle for enhanced visibility in low light conditions.
5. Regularly check the field of view for clarity and make adjustments as necessary.

Disposal Instructions

- Dispose of the riflescope and any related materials in accordance with local regulations.
- Do not dispose of the riflescope in regular household waste.
- Contact local waste management authorities for proper disposal methods.

Contact Information for Further Support

For safety inquiries or additional support regarding the 3-20x50 PM II Ultra Short Riflescope, please consult the manufacturer or authorized dealer. Ensure you have the product details on hand for efficient assistance.

Thank you for prioritizing safety while using your riflescope. Your adherence to these guidelines helps ensure a safe and enjoyable shooting experience.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk