

3-20x50 PM II Ultra Short - 5-20x50 PM II Ultra Short LPI P4FL 1cm ccw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [5-20x50 PM II Ultra Short LPI P4FL 1cm ccw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015808
- Mfr. No.: 173-911-972-G8-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537063745

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides important safety instructions and guidelines to ensure the safe and effective use of your riflescope. Please read this manual carefully before use.

General Safety Guidelines

- Ensure safe use of the riflescope by following all instructions provided in this guide.
- Be aware of potential hazards associated with the use of riflescopes, including but not limited to improper handling, misuse, and environmental conditions.
- Always handle the riflescope with care to avoid damage and ensure optimal performance.
- Store the riflescope in a safe place, out of reach of children and vulnerable individuals.
- Regularly check for updates on product safety and recalls through official channels.

Specific Safety Precautions for Use

- Always use the riflescope in accordance with local laws and regulations regarding firearms and shooting.
- Ensure that the riflescope is securely mounted to the firearm before use.
- Avoid looking directly at the sun or powerful light sources through the riflescope, as this may cause permanent eye damage.
- Do not disassemble or modify the riflescope in any way, as this may compromise its safety and functionality.
- Be mindful of your surroundings and ensure a clear line of sight when using the riflescope to prevent accidents.

Instructions for Installation and Usage

1. Mounting the Riflescope:

- Select a suitable mounting base compatible with the 34 mm main tube.
- Securely fasten the riflescope to the firearm using appropriate mounting rings or clamps.
- Ensure that the riflescope is level and properly aligned with the firearm's barrel.

2. Adjusting the Settings:

- Familiarize yourself with the magnification range (3-20x) and the adjustment features of the riflescope.
- Adjust the side parallax from approximately 25 m to infinity as needed for your shooting distance.
- Set the illuminated reticle to the desired brightness level for optimal visibility.

3. Using the Riflescope:

- Position your eye at the correct distance (approximately 90 mm) from the eyepiece to avoid recoil injuries.
- Use the field of view (approx. 13.0-2.1 m at 100 m) to gain situational awareness before taking a shot.
- Maintain a stable shooting position and control your breathing for improved accuracy.

Disposal Instructions

- Dispose of the riflescope and its components in accordance with local regulations for electronic waste and hazardous materials.
- Do not dispose of the riflescope in regular household waste.
- Contact local waste disposal authorities for guidance on proper disposal methods.

Contact Information for Further Support

For any safety inquiries or support related to the 3-20x50 PM II Ultra Short Riflescope, please refer to the official Schmidt and Bender website or contact your local authorized dealer.

By adhering to these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your riflescope. Thank you for your attention to these important matters.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk