

3-20x50 PM II Ultra Short - 5-20x50 PM II Ultra Short LPI P4FL 1cm ccw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [5-20x50 PM II Ultra Short LPI P4FL 1cm ccw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015811
- Mfr. No.: 173-911-972-F1-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537063684

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope by Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure safe and effective usage of your riflescope. Please read through this document carefully to understand the safety precautions and usage instructions.

General Safety Guidelines

- Always handle the riflescope with care to avoid damage.
- Ensure that the riflescope is mounted securely to your firearm before use.
- Never look directly at the sun through the riflescope, as it can cause serious eye damage.
- Keep the riflescope clean and free from moisture to maintain optimal performance.
- Store the riflescope in a cool, dry place when not in use.
- Regularly check for any signs of wear or damage to the riflescope and replace as necessary.
- Follow all local laws and regulations regarding the use of firearms and riflescopes.

Specific Safety Precautions for Use

- Ensure that the riflescope is only used by individuals who are trained and knowledgeable in firearm safety.
- Always keep the firearm pointed in a safe direction when handling.
- Use appropriate eye and ear protection when shooting.
- Be aware of your surroundings and ensure that there is a clear line of sight when aiming.
- Do not use the riflescope if it has been damaged or if there are any concerns about its functionality.
- Ensure that the riflescope is adjusted correctly for your specific shooting conditions.

Instructions for Installation and Usage

Installation

1. **Choose a Suitable Mount:** Select a mounting system that is compatible with the 34 mm main tube of the riflescope.
2. **Secure Mounting:** Attach the riflescope to the firearm using the chosen mount. Ensure that all screws are tightened to the manufacturer's specifications.
3. **Check Alignment:** Make sure the riflescope is aligned with the barrel of the firearm for accurate shooting.
4. **Adjust for Eye Relief:** Position the riflescope so that you have a comfortable eye relief of approximately 90 mm.

Usage

1. **Adjust Magnification:** Use the magnification ring to set the desired level between 3x and 20x.
2. **Focus the Reticle:** Adjust the focus of the reticle by turning the appropriate dial until the reticle appears sharp.
3. **Set Parallax:** Adjust the side parallax setting according to the distance of your target (from approx. 25 m to infinity).
4. **Check Elevation and Windage:** Use the lowprofile elevation turret to make necessary adjustments for windage and elevation.
5. **Maintain Situational Awareness:** Keep an eye on your surroundings while using the riflescope to ensure safety.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical devices.
- Remove batteries (if applicable) and dispose of them separately in designated recycling bins.
- Do not dispose of the riflescope in regular household waste.

Contact Information for Further Support

For any safety inquiries or further support, please refer to the manufacturer's contact information provided with your product packaging.

By following these safety instructions, you can maximize the performance and longevity of your 3-20x50 PM II Ultra Short Riflescope while ensuring safe usage. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk