

3-20x50 PM II Ultra Short - 5-20x50 PM II Ultra Short LPI MSR2 1cm cw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [5-20x50 PM II Ultra Short LPI MSR2 1cm cw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015815
- Mfr. No.: 173-945-862-G9-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537063912

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope by Schmidt and Bender. This guide provides essential safety information and instructions to ensure the safe and effective use of your riflescope. Please read this manual carefully before using the product to understand the safety precautions, installation procedures, and proper usage guidelines.

General Safety Guidelines

- Ensure the riflescope is used only for its intended purpose.
- Always handle the riflescope with care to prevent damage.
- Keep the riflescope out of reach of children and vulnerable individuals.
- Regularly inspect the riflescope for any signs of damage or wear before use.
- Do not attempt to disassemble or modify the riflescope.
- Always follow local laws and regulations regarding the use of firearms and optics.
- Be aware of your surroundings and ensure a clear line of sight when using the riflescope.

Specific Safety Precautions for Use

- **Magnification Caution:** The 3-20x magnification allows for detailed observation. Avoid using high magnification in unstable conditions.
- **Eye Relief:** Maintain a distance of approximately 90 mm from the eyepiece to prevent injury from recoil.
- **Light Conditions:** Use the riflescope in adequate light conditions to ensure optimal visibility and safety.
- **Parallax Adjustment:** Adjust the parallax setting according to the distance of your target to enhance accuracy and safety.
- **Reticle Illumination:** Use the illuminated reticle responsibly, especially in lowlight conditions, to avoid distractions and maintain focus on your target.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting platform that is compatible with the riflescope.
- Securely attach the riflescope to the rifle using appropriate rings and bases.
- Ensure that the riflescope is level and aligned with the rifle's barrel.

2. Adjustment:

- Adjust the elevation and windage turrets to zero the riflescope according to your shooting requirements.
- Set the parallax adjustment based on the target distance (from approx. 25 m to infinity).

3. Usage:

- Before shooting, ensure that the area is clear of people and obstacles.
- Use proper shooting stance and grip to stabilize the rifle.
- Focus on your target through the riflescope and adjust the magnification as needed.
- Maintain awareness of your surroundings while aiming and shooting.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations for electronic and optical equipment.
- Do not dispose of the riflescope in household waste. Check for designated recycling centers or hazardous waste disposal facilities.

Contact Information for Further Support

For any inquiries or further support regarding the 3-20x50 PM II Ultra Short Riflescope, please refer to the manufacturer's official website or contact your local retailer.

By following these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your 3-20x50 PM II Ultra Short Riflescope. Thank you for your attention to safety and responsible usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk