

# 3-20x50 PM II Ultra Short - 5-20x50 PM II Ultra Short LPI TREMOR5 1cm cw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×  
Objective Lens Diameter: 50 mm  
Main Tube Diameter: 34 mm  
Field of View: approx. 13.0–2.1 m @100 m  
Exit Pupil: approx. 11.4–2.5 mm  
Eye Relief: approx. 90 mm  
Length: approx. 340 mm  
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

## Attributes

- Name: [5-20x50 PM II Ultra Short LPI TREMOR5 1cm cw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015816
- Mfr. No.: 173-945-562-G9-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537063905

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

# Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

## Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope by Schmidt and Bender. This guide provides essential safety instructions to ensure the safe use of this product. By following these guidelines, you can maximize your experience while minimizing risks associated with the use of this highperformance riflescope.

## General Safety Guidelines

- Always handle the riflescope with care to avoid damage.
- Ensure that the riflescope is mounted securely to your firearm before use.
- Use the riflescope only for its intended purpose, which is to enhance your shooting experience.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or wear. If any issues are detected, discontinue use immediately.
- Always adhere to local laws and regulations regarding the use of firearms and optical devices.

## Specific Safety Precautions for Use

- **Eye Protection:** Always wear appropriate eye protection when using firearms equipped with the riflescope.
- **Environment:** Use the riflescope in safe and suitable environments. Avoid using it in wet or extreme weather conditions unless it is specifically rated for such use.
- **Shooting Range Etiquette:** Follow all safety rules and guidelines at shooting ranges. Ensure that the area is clear of other individuals before aiming and firing.
- **Adjustments:** Make adjustments to the riflescope settings only when the firearm is pointed in a safe direction.
- **Maintenance:** Clean the riflescope according to the manufacturer's instructions to maintain optimal performance. Use only recommended cleaning materials.

## Instructions for Installation and Usage

### 1. Mounting the Riflescope:

- Choose a suitable mounting platform on your firearm that is compatible with the 34 mm main tube diameter.
- Secure the riflescope firmly using the appropriate tools. Ensure it is level and aligned with the barrel.

### 2. Focusing the Reticle:

- Adjust the side parallax setting according to your shooting distance, from approximately 25 m to infinity.
- Use the diopter adjustment to focus the reticle to your eyesight.

### 3. Setting the Magnification:

- Rotate the magnification ring to set the desired level between 3x and 20x. Ensure the setting is appropriate for your shooting distance.

### 4. Using the Elevation Turret:

- Make adjustments to the elevation turret for precise shooting. Ensure it is locked in place after adjustments.

#### **5. Field of View:**

- Be aware that the field of view spans approximately 13.0–2.1 m at 100 m. Adjust your position accordingly for optimal visibility.

#### **6. Exit Pupil and Eye Relief:**

- Maintain a proper distance from the eyepiece to ensure optimal image clarity and comfort. The exit pupil ranges from approximately 11.4–2.5 mm, and the eye relief is about 90 mm.

## **Disposal Instructions**

- Dispose of the riflescope according to local regulations regarding electronic and optical devices.
- Do not dispose of the riflescope in regular household waste. Instead, take it to a designated electronic waste recycling center.

## **Contact Information for Further Support**

For any questions or safety inquiries regarding the 3-20x50 PM II Ultra Short Riflescope, please refer to the manufacturer's contact point provided with your product documentation.

By following these safety instructions, you can ensure a safe and enjoyable experience with your riflescope. Thank you for your attention to these important guidelines.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)