

3-20x50 PM II Ultra Short - 5-20x50 PM II Ultra Short LPI TREMOR5 1cm cw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [5-20x50 PM II Ultra Short LPI TREMOR5 1cm cw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015819
- Mfr. No.: 173-945-562-F2-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537063844

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope by Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your riflescope. Please read this document carefully before installation and use.

General Safety Guidelines

- Ensure safe use of the riflescope by following all instructions.
- Be aware of potential hazards associated with improper handling and use.
- Regularly check for updates and recalls on the EU's Safety Gate platform.
- Report any unsafe products or accidents to the appropriate authorities.
- Ensure that the product is suitable for the intended user, especially when used by children or vulnerable individuals.
- Maintain awareness of your surroundings when using the riflescope, particularly in outdoor environments.

Specific Safety Precautions for Use

- Always use the riflescope in a safe and controlled environment.
- Ensure the riflescope is securely mounted on the firearm before use.
- Avoid looking directly at the sun or any bright light source through the riflescope.
- Do not attempt to disassemble or modify the riflescope in any way.
- Always treat every firearm as if it is loaded, and follow all firearm safety guidelines.
- Ensure that the riflescope is used only by individuals trained in the safe handling of firearms.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting platform on your firearm that is compatible with the 34 mm main tube of the riflescope.
- Securely attach the riflescope to the mounting platform using appropriate rings and tools.
- Ensure the riflescope is level and aligned with the firearm's barrel before tightening the mounting rings.

2. Usage:

- Adjust the magnification by rotating the magnification ring to the desired level within the 3-20x range.
- Use the side parallax adjustment to set the focus from approximately 25 m to infinity for optimal clarity.
- Ensure the eye relief of approximately 90 mm is maintained for comfortable viewing.
- Use the illuminated reticle feature as necessary, ensuring that the illumination level is appropriate for the lighting conditions.
- Always check the field of view to maintain situational awareness, especially at lower magnifications.

Disposal Instructions

- Follow local regulations for the disposal of optical devices.
- Do not dispose of the riflescope in regular household waste.
- Consider recycling options for materials that can be repurposed.
- If the product is deemed unsafe or damaged, contact the manufacturer for guidance on proper disposal methods.

Contact Information for Further Support

For safety inquiries or further support, please refer to the manufacturer's website or customer service resources. It is important to have access to reliable information regarding product safety and use.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 3-20x50 PM II Ultra Short Riflescope. Always prioritize safety and responsible use when handling firearms and optical devices.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk