

3-20x50 PM II Ultra Short - 5-20x50 PM II Ultra Short LPI TREMOR5 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [5-20x50 PM II Ultra Short LPI TREMOR5 1cm ccw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015825
- Mfr. No.: 173-945-562-F1-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537063813

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your riflescope. Please read this manual carefully before using the product to maximize your safety and performance.

General Safety Guidelines

- Ensure that the riflescope is used only for its intended purpose.
- Always handle the riflescope with care to avoid damage.
- Keep the riflescope out of reach of children and vulnerable individuals.
- Regularly inspect the riflescope for any signs of wear or damage before use.
- Follow all local laws and regulations regarding the use of firearms and optics.
- Use appropriate eye protection when using the riflescope.

Specific Safety Precautions for Use

- Avoid looking directly at the sun through the riflescope, as it may cause permanent eye damage.
- Do not disassemble the riflescope; it is a sealed unit designed for optimal performance.
- Ensure that the riflescope is securely mounted to the firearm to prevent accidents.
- When adjusting the magnification or reticle settings, do so only when the firearm is pointed in a safe direction.
- Be aware of your surroundings and ensure that the area is clear of people or obstacles before firing.

Instructions for Installation and Usage

1. Installation

- Select a suitable mounting platform for your riflescope.
- Ensure that the mounting rings are compatible with the 34 mm main tube diameter.
- Securely attach the riflescope to the firearm according to the manufacturer's mounting instructions.
- Confirm that the riflescope is level and aligned with the firearm.

2. Usage

- Adjust the magnification by rotating the magnification ring to your desired level (3-20x).
- To adjust the side parallax, locate the parallax adjustment knob and set it according to your target distance.
- Use the elevation turret to set the appropriate elevation for your shooting distance.
- Utilize the illuminated reticle feature as needed, ensuring that the battery is installed correctly.
- Maintain a comfortable eye relief of approximately 90 mm while aiming through the riflescope.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical devices.
- Do not dispose of the riflescope in regular household waste.
- If the riflescope is damaged or no longer functional, consider recycling options available in your area.

Contact Information for Further Support

For any inquiries regarding the safety and use of the 3-20x50 PM II Ultra Short Riflescope, please refer to the manufacturer's website or contact your local retailer for assistance.

Conclusion

By following these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your 3-20x50 PM II Ultra Short Riflescope. Always prioritize safety and compliance with local regulations when using firearms and optical devices. Thank you for your attention to safety!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk