

3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 1cm cw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP P4FL 1cm cw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015932
- Mfr. No.: 669-911-972-G9-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064827

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power Tactical Riflescope](#)
- [About Us](#)

Safety Instruction Guide for 3-27x56 PM II High Power Tactical Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Tactical Riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure safe and effective use of your riflescope. Please read this document carefully before using the product.

General Safety Guidelines

- Ensure that the riflescope is used only for its intended purpose.
- Always handle the riflescope with care to avoid damage and ensure safety.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or malfunction.
- Do not attempt to disassemble or modify the riflescope, as this may void the warranty and pose safety risks.
- Follow all local laws and regulations regarding the use of firearms and optical devices.

Specific Safety Precautions for Use

- Use the riflescope only on firearms that are compatible with its specifications.
- Always ensure that the firearm is unloaded when mounting or adjusting the riflescope.
- Avoid looking directly at the sun through the riflescope, as this can cause severe eye damage.
- Maintain a proper shooting stance and ensure a clear line of sight before taking aim.
- Be aware of your surroundings and ensure that your target and the area beyond are safe before shooting.
- Use appropriate protective eyewear when using the riflescope, especially in outdoor environments.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded and safe.
- Mount the riflescope securely on the firearm using the appropriate mounting rings.
- Adjust the positioning of the riflescope to achieve a comfortable eye relief of approximately 90 mm.
- Tighten the mounting screws carefully to avoid overtightening, which may damage the scope.

2. Usage:

- Adjust the magnification by rotating the magnification dial to select the desired level (3-27x).
- Use the parallax adjustment to finetune the focus based on your distance from the target (10 m to infinity).
- Make elevation and windage adjustments using the turret system, ensuring to note the click values (approx. 0.1 mrad).
- Always check the field of view and exit pupil to ensure optimal visibility and clarity.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations for electronic and optical devices.
- Do not dispose of the riflescope in regular household waste.
- If the riflescope is damaged or no longer functional, contact a professional for proper disposal methods.

Contact Information for Further Support

For any safety inquiries or further assistance regarding your riflescope, please reach out to the designated EU contact point or authorized dealer.

Thank you for your attention to these safety guidelines. Your safety and the safety of others is paramount when using the 3-27x56 PM II High Power Tactical Riflescope.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk