

3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 1cm cw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP P4FL 1cm cw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015936
- Mfr. No.: 669-911-972-F2-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064926

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure safe and effective use of the product. Please read this document carefully before using the scope.

General Safety Guidelines

- Ensure that the product is used in accordance with the manufacturer's instructions.
- Store the riflescope in a safe place, away from children and unauthorized users.
- Regularly inspect the scope for any signs of damage or wear.
- Do not attempt to disassemble or modify the scope.
- Always use the riflescope in a safe environment, free from distractions and hazards.
- Use appropriate protective gear (e.g., eye protection) when using firearms equipped with this scope.
- Report any unsafe conditions or product defects to the relevant authorities.

Specific Safety Precautions for Use

- Ensure that the riflescope is securely mounted to the firearm before use.
- Avoid looking directly at the sun or any bright light source through the scope.
- Be aware of your surroundings and ensure a safe shooting environment at all times.
- Always treat firearms as if they are loaded and follow standard firearm safety rules.
- Keep the riflescope clean and free of obstructions to maintain optimal performance.
- Do not use the scope for purposes other than its intended use, such as a viewing device for nonshooting activities.

Instructions for Installation and Usage

1. Installation

- Ensure the firearm is unloaded before installation.
- Use appropriate mounting rings compatible with the 34 mm main tube of the scope.
- Align the scope with the firearm's barrel to ensure accuracy.
- Tighten the mounting screws securely but avoid overtightening, which may damage the scope.

2. Usage

- Adjust the magnification according to your shooting distance and target size.
- Use the turret system to make precise adjustments for elevation and windage.
- Check the parallax adjustment to ensure clarity at varying distances.
- Maintain a stable shooting position for optimal accuracy.

Disposal Instructions

- Dispose of the product in accordance with local regulations and guidelines for electronic and optical devices.
- Do not dispose of the product in regular household waste.
- Consider recycling options for materials that can be reused or repurposed.

Contact Information for Further Support

For safety inquiries or product concerns, please refer to the manufacturer's official website or contact your local distributor.

Conclusion

Following these safety guidelines will help ensure a safe and enjoyable experience with your 3-27x56 PM II High Power riflescope. Always prioritize safety and responsibility when using firearms and related equipment.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk