

3-27x56 PM II High Power - 3-27x56 PM II High Power LP GR²ID 1cm cw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP GR²ID 1cm cw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015938
- Mfr. No.: 669-911-422-F2-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064940

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this information carefully to maximize your safety and the performance of the riflescope.

General Safety Guidelines

- **Product Safety:** This product is designed for safe use. Follow all instructions to mitigate risks associated with its operation.
- **Enhanced Recalls:** Be aware that in the event of a product recall, you will receive standardized notices, and remedies will be provided free of charge.
- **Online Shopping Protection:** If you purchased this product online, you have the same safety protections as if you bought it in a physical store.
- **Special Consumer Focus:** Extra care is taken to ensure the safety of vulnerable groups, including children.
- **EU Contact Point:** For safety inquiries, a designated EU-based contact is available (details not included in this guide).
- **Rapid Alerts:** Stay informed about any unsafe products through the EU's Safety Gate system.

Specific Safety Precautions for Use

- **Age Restrictions:** This product is intended for use by individuals aged 18 and older. Keep out of reach of children.
- **Proper Handling:** Always handle the riflescope with care. Avoid dropping or subjecting it to impacts.
- **Environmental Considerations:** Do not expose the riflescope to extreme temperatures, moisture, or corrosive substances.
- **Eye Protection:** Always wear appropriate eye protection when using this riflescope.
- **Mounting:** Ensure the riflescope is securely mounted to your firearm according to the manufacturer's specifications to prevent accidents.
- **Maintenance:** Regularly inspect the riflescope for any signs of damage or wear. Do not use if damaged.

Instructions for Installation and Usage

1. Installation:

- Ensure your firearm is unloaded before installation.
- Use a suitable mounting system compatible with the 34 mm tube diameter.
- Follow the manufacturer's instructions for mounting the riflescope securely.
- Check the alignment of the riflescope to ensure accurate targeting.

2. Usage:

- Adjust the magnification according to your shooting needs, ranging from 3x to 27x.
- Use the turret system for elevation and windage adjustments. Make fine adjustments as necessary.
- To adjust for parallax, set the parallax adjustment knob according to the distance of your target.
- Always confirm your zeroing before engaging in any shooting activities.

3. PostUse Care:

- Clean the lenses with a soft, lintfree cloth to avoid scratches.
- Store the riflescope in a dry and cool place when not in use.
- Avoid exposing the riflescope to direct sunlight for prolonged periods.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical devices.
- **Recycling:** If possible, recycle the product to minimize environmental impact.

Contact Information for Further Support

For any questions or concerns regarding the safety and use of the 3-27x56 PM II High Power riflescope, please refer to your local authorized Schmidt and Bender dealer or visit the official website for more resources and support.

By following these safety instructions, you can ensure a safe and enjoyable experience with your Schmidt and Bender riflescope. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk