

# 3-27x56 PM II High Power - 3-27x56 PM II High Power LP TREMOR3 1cm cw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

## Attributes

- Name: [3-27x56 PM II High Power LP TREMOR3 1cm cw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015939
- Mfr. No.: 669-911-532-F2-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064919

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

# Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

## Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope from Schmidt and Bender. This guide provides important safety instructions and guidelines to ensure safe and effective use of your riflescope. Please read this manual carefully before using the product.

## General Safety Guidelines

- Always handle the riflescope with care to avoid damage.
- Ensure that the riflescope is mounted securely before use.
- Use the riflescope only for its intended purpose.
- Keep the riflescope out of reach of children and vulnerable individuals.
- Regularly inspect the riflescope for signs of wear or damage.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about product recalls and safety updates through the EU Safety Gate platform.

## Specific Safety Precautions for Use

- **Eye Safety:** Always use protective eyewear when using the riflescope to prevent eye injuries.
- **Mounting:** Ensure that the riflescope is mounted according to the manufacturer's instructions to avoid misalignment.
- **Adjustment:** Be cautious when adjusting the turrets; make small adjustments to avoid sudden movements that could lead to accidents.
- **Parallax Adjustment:** Adjust the parallax setting carefully based on your target distance to maintain accuracy.
- **Weather Conditions:** Avoid using the riflescope in extreme weather conditions, such as heavy rain or strong winds, which may affect performance.
- **Transport:** Use a protective case when transporting the riflescope to prevent damage.
- **Cleaning:** Use a soft, lintfree cloth for cleaning the lenses. Avoid using harsh chemicals or abrasive materials.

## Instructions for Installation and Usage

### 1. Mounting the Riflescope:

- Select a suitable mounting base compatible with your firearm.
- Follow the manufacturer's instructions for mounting the riflescope securely.
- Ensure the riflescope is level and aligned with the barrel.

### 2. Adjusting the Turrets:

- To adjust for windage and elevation, use the turret adjustments. Refer to the specifications for click values.
- Make adjustments gradually and test the alignment at a safe distance.

### 3. Setting the Parallax:

- Adjust the parallax setting based on the distance of your target.
- Ensure the setting is accurate to maintain clarity and precision.

#### **4. Using the Reticle:**

- Familiarize yourself with the reticle design and its functionalities.
- Use the reticle for accurate aiming and target acquisition.

#### **5. Regular Maintenance:**

- Check the mounting and adjustments regularly to ensure they remain secure.
- Clean the lenses as needed to maintain clarity.

## **Disposal Instructions**

- Dispose of the riflescope responsibly at a designated electronic waste recycling facility.
- Do not dispose of the product in regular household waste.
- Follow local regulations for the disposal of electronic equipment.

## **Contact Information for Further Support**

For any questions or concerns regarding the safety and use of your 3-27x56 PM II High Power Riflescope, please reach out to the appropriate support channels as indicated by the retailer or manufacturer.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)