

3-27x56 PM II High Power - 3-27x56 PM II High Power LP MSR2 1cm cw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP MSR2 1cm cw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015941
- Mfr. No.: 669-911-842-M3-I6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537043334

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope from Schmidt and Bender. This guide provides important safety instructions and guidelines to ensure safe and effective use of your riflescope. Please read this document carefully before using the product.

General Safety Guidelines

- Ensure that the riflescope is used only for its intended purpose, which is for precision shooting and hunting.
- Always handle the riflescope with care to avoid damage.
- Ensure that the riflescope is securely mounted on your firearm before use.
- Keep the riflescope away from children and unauthorized users.
- Regularly inspect the riflescope for signs of wear or damage. Do not use if damaged.
- Follow all local laws and regulations regarding the use of firearms and riflescopes.

Specific Safety Precautions for Use

- Always ensure the firearm is unloaded when attaching or detaching the riflescope.
- Avoid looking directly at the sun or any bright light source through the riflescope, as this may cause permanent eye damage.
- Use the riflescope only in safe shooting environments, away from people and animals.
- Be aware of your surroundings and ensure a clear line of sight before taking a shot.
- Do not modify the riflescope in any way, as this may compromise its safety and performance.
- Always use appropriate eye protection when using firearms equipped with the riflescope.

Instructions for Installation and Usage

1. Installation

- Ensure the firearm is unloaded.
- Mount the riflescope securely on the firearm using appropriate rings and bases.
- Tighten all mounting screws according to the manufacturer's specifications.
- Check the alignment of the reticle before use.

2. Usage

- Adjust the magnification according to your shooting requirements.
- Use the turret system for elevation and windage adjustments, ensuring fine clicks for precise targeting.
- Check the parallax adjustment to ensure accuracy at varying distances.
- Maintain proper eye relief for a comfortable and safe viewing experience.
- Regularly clean the lenses with a soft cloth and lens cleaner to maintain clarity.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations for electronic and optical devices.
- Do not dispose of the riflescope in regular household waste.
- Consider recycling options where available.

Contact Information for Further Support

For any questions or concerns regarding the safety and use of the 3-27x56 PM II High Power Riflescope, please refer to the manufacturer's website or contact their support team directly.

Conclusion

By following these safety instructions and guidelines, you can ensure a safe and enjoyable experience with your 3-27x56 PM II High Power Riflescope. Always prioritize safety and compliance with local laws when using firearms and related equipment.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk