

# 3-27x56 PM II High Power - 3-27x56 PM II High Power LP TREMOR3 1cm cw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

## Attributes

- Name: [3-27x56 PM II High Power LP TREMOR3 1cm cw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015943
- Mfr. No.: 669-911-532-M3-I6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537043280

NO IMAGE  
AVAILABLE

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

# Safety Instruction Guide for 3-27x56 PM II High Power

## Introduction

Thank you for choosing the 3-27x56 PM II High Power from Schmidt and Bender. This tactical riflescope is designed for precision and versatility in various shooting scenarios. To ensure safe and effective use, please read and follow these safety instructions carefully.

## General Safety Guidelines

- **Product Safety:** This product is designed to meet EU safety standards. Ensure proper handling and usage to avoid risks.
- **Enhanced Recalls:** Stay informed about any product recalls. If a recall is issued, follow the provided instructions for safe return or remedy.
- **Online Shopping:** Ensure that you purchase this product from authorized retailers that comply with safety regulations.
- **Special Consumer Focus:** This product is not intended for use by children. Always supervise its use in environments where children are present.
- **EU Contact Point:** For safety inquiries, refer to the contact information provided by your retailer or manufacturer.
- **Rapid Alerts:** Regularly check the EU's Safety Gate platform for updates on any safety concerns related to this product.

## Specific Safety Precautions for Use

- **Avoid Direct Eye Exposure:** Do not look directly into the scope while it is pointed at a light source; this can cause eye damage.
- **Secure Mounting:** Ensure that the scope is securely mounted to the rifle to prevent accidents during use.
- **Weather Considerations:** Avoid using the scope in extreme weather conditions that may affect visibility or performance.
- **Proper Handling:** Always handle the scope with care. Avoid dropping or subjecting it to strong impacts.
- **Cleaning:** Use only recommended cleaning materials to avoid scratching the lenses or damaging the scope's finish.

## Instructions for Installation and Usage

### 1. Installation:

- Ensure you have a compatible mounting system for the 34 mm main tube diameter.
- Securely attach the scope to the rifle using the appropriate mounting rings.
- Check alignment and adjust as necessary to ensure optimal performance.

### 2. Usage:

- Adjust the magnification according to your target distance using the zoom dial.
- Use the parallax adjustment feature to enhance accuracy based on target distance.
- Regularly check the turret settings for elevation and windage to maintain accuracy.
- Maintain a comfortable eye relief of approximately 90 mm for optimal viewing.

## **Disposal Instructions**

- Dispose of the product in accordance with local regulations regarding electronic waste.
- Do not dispose of the product in regular household waste. Instead, take it to a designated electronic waste recycling center.

## **Contact Information for Further Support**

For any questions or concerns regarding the 3-27x56 PM II High Power, please refer to the contact information provided by your retailer or manufacturer.

Thank you for your attention to these safety instructions. Enjoy your shooting experience with the 3-27x56 PM II High Power!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)