

3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 0,05 mrad cw MT II MTC LT / DT II+ ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP P4FL 0,05 mrad cw MT II MTC LT / DT II+ ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015944
- Mfr. No.: 669-911-972-I6-H6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537026801

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instructions for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instructions for the 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope from Schmidt and Bender. This manual provides important safety guidelines and instructions to ensure safe and effective use of your riflescope. Please read this document carefully before using the product.

General Safety Guidelines

- Always handle the riflescope with care to avoid damage or injury.
- Ensure the riflescope is mounted securely to prevent it from becoming loose during use.
- Use the riflescope in accordance with local laws and regulations regarding firearms and optics.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or wear. If any issues are found, do not use the product until it has been repaired or replaced.
- Always wear appropriate eye protection when using the riflescope to safeguard against any potential hazards.

Specific Safety Precautions for Use

- Ensure that the riflescope is suitable for your specific firearm and intended use.
- Do not use the riflescope if it has been dropped or subjected to severe impact.
- Avoid exposing the riflescope to extreme temperatures, humidity, or harsh chemicals, as these can damage the optics and internal components.
- When adjusting the turrets, do so gently to avoid damaging the internal mechanisms.
- Be aware of your surroundings and ensure that you have a clear line of sight before aiming the riflescope.
- Never point the riflescope at anything you do not intend to shoot.

Instructions for Installation and Usage

1. Installation:

- Choose a suitable mounting location on your firearm that allows for comfortable eye alignment and aiming.
- Securely attach the riflescope to the mounting base using the appropriate tools, following the manufacturer's instructions.
- Ensure that the riflescope is level and properly aligned with the firearm's barrel.

2. Usage:

- Adjust the magnification according to your target distance and conditions.
- Use the parallax adjustment to ensure a clear image at varying distances.
- Maintain a proper shooting stance and ensure that your eye is aligned with the eyepiece for optimal viewing.
- After use, cover the riflescope with a protective cap to prevent dust and moisture from entering the optics.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical devices.

- If the product is damaged beyond repair, consider recycling the materials where possible to minimize environmental impact.

Contact Information for Further Support

For any safety inquiries or concerns regarding the 3-27x56 PM II High Power Riflescope, please refer to the manufacturer's website or contact your local dealer for assistance.

Important Note: In case of any safety-related incidents or if you encounter any unsafe products, report them to the appropriate authorities immediately. Stay informed about product recalls by checking the EU's Safety Gate platform regularly. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk