

3-27x56 PM II High Power - 3-27x56 PM II High Power LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27×56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27× magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0–1.4 m at 100 m, while the exit pupil ranges around 8.7–2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27×

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27×56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015949
- Mfr. No.: 669-911-532-G8-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064766

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power riflescope from Schmidt and Bender. This guide provides essential safety instructions and usage guidelines to ensure your safety and the optimal performance of your product. Please read this manual carefully before using the riflescope.

General Safety Guidelines

- Ensure safe use of the riflescope by following the instructions provided in this guide.
- Be aware of potential hazards associated with the use of optical devices, including but not limited to:
 - Eye strain from prolonged use.
 - Risks from handling the product improperly.
- Always use the riflescope in a safe environment and be mindful of your surroundings.
- Keep the product out of reach of children and vulnerable individuals to prevent accidental injury.
- Regularly check for updates or recalls related to this product through the EU Safety Gate platform.

Specific Safety Precautions for Use

- Do not look directly at the sun through the riflescope, as this can cause permanent eye damage.
- Ensure the riflescope is securely mounted to your firearm before use.
- Avoid using the product in adverse weather conditions that may impair visibility or safety.
- Maintain a proper shooting stance and ensure a clear line of sight before firing.
- Always handle firearms with care and follow all applicable laws and regulations.

Instructions for Installation and Usage

Installation

- Ensure you have the necessary tools for mounting the riflescope securely.
- Follow these steps for installation:
 1. **Choose a Suitable Mount:** Select a mount compatible with the 34 mm main tube of the riflescope.
 2. **Attach the Mount:** Securely attach the mount to your firearm's rail system.
 3. **Position the Riflescope:** Place the riflescope into the mount and adjust its position for optimal eye relief (approx. 90 mm).
 4. **Tighten the Mount:** Securely tighten all screws to ensure the riflescope is firmly in place.
 5. **Check Alignment:** Confirm that the riflescope is aligned with the barrel of the firearm.

Usage

- Before using the riflescope, familiarize yourself with its features:
 - **Magnification:** Adjust the magnification from 3x to 27x as needed.
 - **Turret System:** Use the turret system for elevation and windage adjustments. Click values are approximately 0.1 mrad.
 - **Parallax Adjustment:** Adjust parallax from around 10 m to infinity for accurate targeting.
- Always perform a safety check before each use:
 - Ensure the firearm is unloaded when mounting or adjusting the riflescope.
 - Verify that the area is clear of obstructions and individuals before aiming or firing.

Disposal Instructions

- Dispose of the riflescope and any associated packaging materials in accordance with local regulations.
- Do not dispose of the product in household waste. Instead, take it to a designated electronic waste recycling facility.
- Ensure that all batteries (if applicable) are disposed of properly according to local battery recycling guidelines.

Contact Information for Further Support

For any inquiries regarding the safety and usage of the 3-27x56 PM II High Power riflescope, please refer to the EU Safety Gate platform for additional information and support resources.

By following these safety instructions, you can ensure a safe and enjoyable experience with your riflescope. Thank you for your attention to these guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk